



## A Stochastic Model for Water Resources Management

Salim Bavandi<sup>1\*</sup> and Seyed Hadi Nasseri<sup>2</sup>

<sup>1</sup> Department of Mathematics, University of Mazandaran, Babolsar, Iran

<sup>2</sup> Department of Mathematical Sciences, University of Mazandaran, Babolsar, Iran

**Received:** 17 June 2017

**Accepted:** 07 August 2017

**Keywords:**

water management

Two-stage stochastic programming

probabilistic programming

stochastic modeling

**Abstract**

Irrigation water management is crucial for agricultural production and livelihood security in many regions and countries throughout the world. Over the past decades, controversial and conflictladen water-allocation issues among competing municipal, industrial and agricultural interests have raised increasing concerns. Particularly, growing population, varying natural conditions and shrinking water availabilities have exacerbated such competitions. Shrinking water availabilities can result in reduced water supplies, while growing population can lead to increased water demands, these two facts can further intensify the water shortage. Stochastic programming methodology is applied in this paper to a capital investment problem in water resources. A framework is offered for the evaluation of electricity generation and water supply for agricultural irrigation. This assessment is conducted through the construction of an appropriate stochastic optimization model. A recursive least squares algorithm is incorporated in the model which enable more accurate estimation of model parameters.

\*Correspondence E-mail: [salimbavandi@yahoo.com](mailto:salimbavandi@yahoo.com)

## INTRODUCTION

Stochastic programming deals with situations where some random parameters appear in a formulation of a mathematical program. Decision models of stochastic programming have been designed to treat the cases when a decision has to be chosen before a realization of random parameters can be observed. Examples of stochastic programming are mathematical programs resulting from such problems as optimizing the stochastic inflows of a reservoir power system (Trezos & Yeh, 1987) using probabilistic models in the design and operation of a reservoir system (Arunkumar & Yeh, 1973) reservoir management and operations models (Yeh, 1985) and others. This paper addresses an application of stochastic programming to a water resource system with a dual-purpose of generating electricity and supplying water for agricultural irrigation. This paper aims to formulate the dual-purpose water resource system as a change-constrained explore the use of recursive least squares filtering (Geib, 1974) in the model, and examine and discuss properties of the model.

With limited water resources for agriculture irrigation, managers tried to identify desired alternatives through raising irrigation productivity to realize optimal water allocation (Ma et al., 2014; Li et al., 2015; Wang et al., 2015) Two-stage stochastic programming (TSP) is effective to deal with problems for which an analysis of policy scenarios is desired and the uncertainties can be expressed as probabilistic distributions. In TSP, an initial decision (first-stage decision) is made based on uncertain future events, then an action can be taken after the pre-regulated disclosure of random variables (second-stage decision) (Li et al., 2006). This implies that TSP can minimize the expected costs of all applicable decisions taken over the two periods. TSP has been widely applied to water resources management over the past few decades (Maqsood et al., 2005; Wang & Huang, 2011).

Generally, in the design and operation of any water reservoir system, the stochastic nature of inflows must be taken into consideration. A multitude of techniques have been employed to model the stochastic inflows to water reservoir systems. In the literature, most researchers have applied stochastic dynamic programming (SDP) for single or multi-reservoir operation optimization. This is because

SDP permits integration of stochastic elements in the model and the sequential nature of the problem. Each optimization technique has its own restriction on the type of constraints it can handle. For instance, a linear program entails all constraints in a linear form, whereas a dynamic program entails that they be expressed as functions of the present, and be independent of the previous variables (see, for example, (Butcher, 1971; Stedinger et al., 1987)). In the study by Stedinger et al. (1984), SDP was used to calculate optimal single reservoir operation.

In this instance, SDP can derive reservoir operating policies which are subject to reliability constraints. A different approach to modeling the system has been applied by Askew (1974), who formulates the problem as a chance-constrained dynamic program (CCDP), an SDP which has the resources to confine the probability of given variables taking on values outside a fixed range. Askew (1974) has also considered the trade-off of benefits and risks associated with long-term reservoir operations. He discusses reliability-constrained dynamic programming that provides control over the probability of failure of the modeled reservoir system. His formulations are based on dynamic programming with discounting. Butcher discusses a multi-purpose single reservoir system extensively. He has devised a deterministic optimal operating policy based on dynamic programming. In his models, sets of deterministic streamflows recur in a Monte Carlo study. Butcher employs a backward dynamic recursive equation using Bellman's Principle of Optimality. The following general formulation is developed by Butcher:

$$f_i(s_i, q_{i+1}) = \max_d \left[ R(d) + \sum_{q_i=0}^{q_i^{max}} P(q_i | q_{i+1}) \cdot f_{i+1}(s_i + q_i - d - e_i, q_i) \right]$$

for all values of  $s_i$  the storage at the start of the second time period and all possible values of inflow during the preceding period  $q_{i+1}$ . There exists a value of the released  $d$  which makes the right-hand side of the model 1 a maximum. This general formulation uses the fact that the inflow in any month is connected to the flow in the preceding month by the conditional probability,  $P(q_i | q_{i+1})$ .  $R(d)$  is the return obtained by releasing a quantity of water  $d$  in the  $i$ th time period, and  $e_i$  is the loss of water in storage by evaporation. Therefore, the general formulation gives  $f_i(s_i, q_{i+1})$ , which is the expected

return from the optimal operation of a system which has time periods to the end of the planning period.

Taylor and Karlin (1984) employ a Markov decision model to a water resource system by specifying the law of motion,  $q(s', q_{i+1})$ . This is a function given when the probability of a particular state  $s'$  being chosen as a joint result of the current state  $s$  and the chosen action  $a$ . In their study, they have defined  $S_n$ , to be the level of water at period  $n$ ,  $A_n$  the amount released during the period, and  $I_n$  the input to the storage system during period  $n$  and based on the probability distribution,  $Pr(I_n=k)=p(k)$  for  $k=0,1,\dots$ . Assumptions are made so that a reservoir has a maximum capacity of  $M$  and that This will lead to the transition law,

$$q(s'|s,a)=Pr\{I_n=s'-s+a\}=p(s'-s+a), \quad \text{if } 0 \leq s' \leq M$$

and

$$q(M|s,a)=Pr\{I_n \geq M-s+a\}=\sum_{s' \geq M} p(s'-s+a).$$

We shall analyze a water resource system similar to that of Taylor and Karlin (1984). Nonetheless, a different approach will be taken to formulate the problem.

## TWO-STAGE STOCHASTIC PROGRAMMING

Two-stage stochastic programming (TSP) refers to a tradeoff between predefined strategies and the associated adaptive adjustments. In TSP, an initial first-stage decision must be made before the random variable is observed, then an action can be taken after the pre-regulated disclosure of second-stage decision. TSP cannot only handle uncertainties expressed as random variables but also provide an effective linkage between the pre-regulated policies and the associated economic implications caused by improper policies. Generally, a TSP model can be formulated as follows:

$$\begin{aligned} \min f &= cx - E[Q(x, \xi)] \\ \text{s.t.} \quad Ax &\leq b, \quad x \geq 0 \end{aligned} \quad (1)$$

Where  $x$  is the first-stage decision made before the random variable is observed,  $\xi$  is the random variable ( $\xi \in \Omega$ ), and  $Q(x, \xi)$  is the optimal value of the following nonlinear programming:

$$\begin{aligned} \min q(y, \xi) \\ \text{s.t.} \quad W(\xi)y &= h(\xi) - T(\xi)x \quad x \geq 0 \end{aligned} \quad (2)$$

where  $y$  is the second-stage adaptive decision, which depends on the realization of the random variable.  $q(y, \xi)$  denotes the secondstage cost function, while  $\{T(\xi), W(\xi), h(\xi) | \xi \in \Omega\}$  are random model parameters with reasonable dimensions, which are functions of the random variable  $\xi$ . The first-stage decision is made before the random variable is observed. Then, when the random variable is observed, the discrepancy that may exist between  $h(\xi)$  and  $T(\xi)x$  corrected by recourse action that minimizes  $q(y, \xi)$  and satisfies  $W(\xi)y = h(\xi) - T(\xi)x, y \geq 0$ . The pre-regulated cost and the potential penalty can thus be taken into account. Therefore, model 1 can be reformulated as follows:

$$\begin{aligned} \max f &= cx - E \left[ \min_{y \geq 0} \{q(y, \xi) | T(\xi)x + W(\xi)y = h(\xi)\} \right] \\ \text{s.t.} \quad Ax &\leq b, \\ x &\geq 0. \end{aligned} \quad (3)$$

Let the random variable  $\xi$  take discrete values  $\xi_l$  with a probability level  $p_l$ , where  $l=1, 2, \dots, n$ . It is assumed that  $p_l > 0$  and  $\sum_{l=1}^n p_l = 1$ . The expected value of the second-stage optimization problem can be expressed as:

$$EQ(x) = E[Q(x, w)] = \sum_{l=1}^n p_l Q(x, \xi_l) \quad (4)$$

For each realization of random variable  $\xi_l$ , a second-stage decision is made, which is denoted by  $y_l$ . The second-stage optimization problem can then be written as:

$$\begin{aligned} \min q(y, \xi) \\ \text{s.t.} \quad W(\xi_l)y &= h(\xi_l) - T(\xi_l)x, \quad \forall l = 1, 2, \dots, n \\ y_l &\geq 0 \end{aligned} \quad (5)$$

Through combining models 4 and 5, model 3 can be reformulated as follows:

$$\begin{aligned} \max f &= cx - \sum_{l=1}^n p_l q(y_l, \xi_l) \\ \text{s.t.} \quad Ax &\leq b, \\ T(\xi_l)x + W(\xi_l)y &= h(\xi_l), \quad \forall l = 1, 2, \dots, n \\ y_l &\geq 0 \end{aligned} \quad (6)$$

## LINEAR PROGRAMMING MODEL TO MAXIMIZE TOTAL PROFIT

This stochastic programming formulation considers probability conditions on constraints. This formulation was first proposed by Revelle et al. (1969) for optimization of a reservoir system. We should use this formulation for a water reservoir system with a dual-purpose of generating electricity and supplying water for agricultural irrigation. The following are definitions of parameters in the system:

$L_n$ : the water level (quantity) at the start of the period  $n$ ,

$Q_n$ : the amount of water released during period  $n$ , i.e., the outflow of water, and

$I_n$ : rainfall to the water reservoir system during period  $n$ , i.e., the inflow.

It is assumed that  $I_n$  is a random variable independent from period to period. In addition, it will be treated as if it is deterministic. To achieve an equilibrium in the system, the following equation must affirm:

$$\text{New Level} = \text{Old Level} + \text{Inflow} - \text{Outflow.} \quad (7)$$

Mathematically

$$L_{n+1} = L_n + I_n - Q_n \quad (8)$$

or

$$L_{n+1} - L_n - Q_n = I_n \quad (9)$$

Assuming that the reservoir has a maximum capacity it follows that

$$L_n \leq M, \text{ for all } n=1, 2, \dots, N \quad (10)$$

and thus,

$$L_{n+1} = \min\{M, L_n + I_n - Q_n\} \quad (11)$$

It is also assumed that there exists a target water level of  $e$  units per period for electrical generation, and that there is no income value for exceeding the target level. Let  $E$  be the unit income for electrical use and  $K$  be the unit penalty for electrical shortages. Hence, the profit from electrical generation,  $E \cdot P_{(n+1)}$ , in period  $n+1$ , is

$$E \cdot P_{n+1} = E \cdot \min\{L_{n+1}, e\} - K \cdot \max\{0, e - L_{n+1}\} \quad (12)$$

It is assumed that water released for irrigation has a unit value of  $W$ . The profit from irrigation in period  $n+1$ ,  $IP_{(n+1)}$  is dependent on the outflow of water during period  $n$ . This relationship is depicted as follows:

$$IP_{n+1} = WQ_n \quad (13)$$

Therefore, the expected total profit in period  $n+1$ ,  $TP_{n+1}$  is sum of model 12 and 13. Mathematically, it is written as follows:

$$TP_{n+1} = E \cdot P_{n+1} + IP_{n+1} = E \cdot \min\{L_{n+1}, e\} - K \cdot \max\{0, e - L_{n+1}\} + W \cdot Q_n \quad (14)$$

We can then formalize the optimization problem given the objective function in model 14 and constraints in 9 and 10. Therefore, the formulation of water reservoir program is

$$\begin{aligned} \max TP_{n+1} &= E \cdot P_{n+1} + IP_{n+1} = E \cdot \min\{L_{n+1}, e\} - K \cdot \max\{0, e - L_{n+1}\} + W \cdot Q_n \\ \text{s.t.} \quad &L_{n+1} - L_n + Q_n = I_n \\ &L_n \leq M, \\ &Q_n, I_n, L_n, L_{n+1} \geq 0, \quad n = 1, \dots, N \end{aligned} \quad (15)$$

However, the objective function in model 2 is not linear. Hence, to 15, we shall define

$$W_{n+1} = \min\{L_{n+1}, e\}, \quad (16)$$

so that

$$W_{n+1} \leq L_{n+1} \quad (17)$$

and

$$W_{n+1} \leq e, \quad (18)$$

Also, by defining

$$X_{n+1} = \max\{0, e - L_{n+1}\}, \quad (19)$$

It follows that

$$X_{n+1} \geq 0, \quad (20)$$

and

$$X_{n+1} \geq e - L_{n+1} \quad (21)$$

Holds. Given the new characterizations, 15 become a simple LP model. Consequently,

$$\begin{aligned} \max \quad & TP_{n+1} = E.W_{n+1} - K.X_{n+1} + W.O_n \\ \text{s.t.} \quad & L_{n+1} - L_n + O_n = I_n, \\ & X_{n+1} + L_{n+1} \geq e, \\ & W_{n+1} \leq e, \\ & L_n \leq M, \\ & O_n, W_{n+1}, L_n, L_{n+1}, X_{n+1}, \quad n = 1, \dots, N. \end{aligned} \quad (22)$$

### UNCERTAINTY ABOUT PARAMETERS OF A THEORETICAL DISTRIBUTION

In our previous discussion, we have treated  $I_n$  as deterministic. However, in this case, we are considering rainfall  $I_n$  to be a random variable with an arbitrary distribution with mean  $\mu$  and variance  $\sigma^2$  and that the observations are independent. Therefore, summing the following constraint

$$L_{n+1} - L_n + O_n = I_n \quad (23)$$

from 1 to some will result in the following equation

$$\sum_{n=1}^k (L_{n+1} - L_n + O_n) = \sum_{n=1}^k I_n \quad (24)$$

$$L_{k+1} - L_1 + \sum_{n=1}^k (O_n) = \sum_{n=1}^k I_n \quad (25)$$

For a sufficiently large  $k$ ,  $\sum_{n=1}^k I_n$  is normally distributed by the Central Limit Theorem. Dividing both sides of model 25 by  $k$ , we shall obtain the following result:

$$\frac{L_{k+1} - L_1}{k} + \frac{1}{k} \cdot \sum_{n=1}^k O_n = \frac{1}{k} \cdot \sum_{n=1}^k I_n \quad (26)$$

We can further simplify model 26 to

$$\frac{L_{k+1} - L_1}{k} + \bar{O}_k = \bar{I}_k \quad (27)$$

where

$$\bar{O} = \frac{1}{k} \cdot \sum_{n=1}^k O_n \quad (28)$$

$$\bar{I} = \frac{1}{k} \cdot \sum_{n=1}^k I_n \quad (29)$$

Given these criteria, kindependent and identically distributed random variables, 22 can be represented as a linear system with linear constraints, the presumption of maximum admissible probabilities of inflows can be managed by chance-constrained linear programming (CLP) techniques. These techniques were first consummated by Charnes and Cooper (1963) and have been illustrated by Revelle et al. (1969):

$$\begin{aligned} \max Z &= c^T x, \\ \text{s.t.} \quad & Ax = b, \\ & P[Tx \geq p] \geq \alpha, \\ & x \geq 0 \end{aligned} \quad (\text{CLP})$$

Where  $P[0]$  denotes probability,  $\alpha$  is a constant vector,  $c$  is cost coefficient vector,  $b$  is a right-hand side vector,  $A$  and  $T$  are coefficient matrices, and lastly,  $x$  is a decision vector.

### THE PROBABILISTIC MODEL

For a dual-purpose water reservoir system, a chance-constrained stochastic program is appropriate and is formulated as follows:

$$\begin{aligned} \max \quad & TP_{k+1} = E.W_{k+1} - K.X_{k+1} + W.O_k, \\ \text{s.t.} \quad & P\{L_{k+1} + O_k \leq \sum_{n=1}^k I_n - \gamma_{k-1}\} \geq 1 - \alpha, \\ & X_{k+1} + L_{k+1} \geq e, \\ & W_{k+1} \leq e, \\ & W_{k+1} - L_{k+1} \leq 0, \\ & L_{k+1} \leq M, \\ & L_{k+1}, X_{k+1}, O_k \geq 0, \quad k = 1, 2, \dots \end{aligned} \quad (\text{PWRP})$$

where  $\gamma_{k-1}$  is equal to  $\sum_{n=1}^{(k-1)} O_n - L_1$  and is constant because sample data are known.  $1 - \alpha$  is the level of significance.

The above probabilistic water reservoir program (PWRP) is equivalent to a deterministic model which is a linear program.

### THE DETERMINISTIC MODEL

Our procedure in using rainfall data samples to estimate the parameter  $p$  will follow the recursive least-squares approach. This algorithm will enable us to recursively revise the estimate at time  $k$  to reflect the most recent data sample obtained in period  $k+1$ . The parameter  $cr$ , on the other hand, is estimated from the maximum likelihood

formula for nonoverlapping blocks of data samples as shown below. Given most recent estimates of the parameters, we then use this information to formulate a deterministic model.

Since there may be zero rainfalls for several periods, the variance estimate should be based on a sufficiently large block of data. To compute the variance of the rainfall variable for every block of some k data points, we use the maximum likelihood estimation formula

$$\begin{aligned} \sigma_k^2 &= \frac{1}{k-1} \sum_{n=1}^k (I_n - \bar{I}_k)^2 \\ \sigma_{2k}^2 &= \frac{1}{k-1} \sum_{n=k+1}^{2k} (I_n - \bar{I}_{2k})^2, \dots, \end{aligned} \quad (30)$$

where

$$\bar{I}_{2k} = \frac{1}{k} \sum_{n=k+1}^{2k} I_n. \quad (31)$$

Assume that we have a historical (a priori) estimate of the variance, and that the updating will be done at the sample periods  $t_k$ ,  $k=1, 2, 3$  and so on. A simple method for updating the sample variance for period t from the last available value  $\sigma_{(t-1)}^2$  is through the exponential smoothing formula

$$\begin{aligned} \sigma_1^2 &= \sigma_0^2 + \lambda(\sigma_k^2 - \sigma_0^2), \\ \sigma_2^2 &= \sigma_1^2 + \lambda(\sigma_{2k}^2 - \sigma_1^2), \\ &\vdots \\ \sigma_t^2 &= \sigma_{t-1}^2 + \lambda(\sigma_{tk}^2 - \sigma_{t-1}^2), \dots, \end{aligned} \quad (32)$$

where  $\lambda$  is the smoothing constant which assumes a value in the range  $[0,1]$ .

The recursive least-squares method for updating the mean parameter  $\mu$  of the rainfall distribution does not require normality in the data. The properties of the updated estimates  $\mu \hat{n} (+)$  are unbiasedness and minimum variance. The plus symbol in  $\mu \hat{n} (+)$  denotes that it is a posterior estimate. Thus the prior estimate, before the measurement  $I_n$  is received, is denoted by  $\mu \hat{n} (-)$ .

The recursive updating formula for the mean is given as follows:

$$\hat{\mu}_n(+)=\hat{\mu}_n(-)+\frac{S_n^z}{\sigma_f^2}\{I_n-\hat{\mu}_n(-)\}, \quad (33)$$

where  $\sigma_f^2$  is the most recent estimate of the variance by the block approach in Eq. 32 and  $S_n^2 (+)=E [\mu \hat{n} (+)-\mu]^2$  posterior error variance of

the mean estimate  $S_n^2 (+)$  can be recursively computed from the prior,  $S_n^2 (-)=E [\mu \hat{n} (-)-\mu]^2$  by the recursive equation

$$\frac{1}{S_n^2(+)}=\frac{1}{S_n^2(-)}+\frac{1}{\sigma_f^2}, \quad n=1,2, \dots, k, \dots, 2k, \dots \quad (34)$$

and  $t=0$  for  $n < k$ ,  $t=1$  for  $k < n < 2k, \dots$ .

To start the recursive algorithm, we need some unbiased estimates  $S_n^2 (-)$ ,  $\mu \hat{1} (-)$  and  $\sigma_0^2$ . We will employ the posterior estimate,  $\mu \hat{n} (+)$ , and  $\sigma_t^2$  in the deterministic model for sequential planning of the dual-purpose water resource system.

We can now proceed to formulate a deterministic model in terms of the posterior estimates from the above algorithm:

$$\max \quad TP_{n+1}=E.W_{n+1}-K.X_{n+1}+W.O_n,$$

$$\text{s.t.} \quad L_{n+1}+O_n \geq n \hat{\mu}_n(+)+z_{1+\alpha} \sqrt{n} \sigma_t-\gamma_{n-1},$$

$$X_{n+1}+L_{n+1} \geq e, \quad (\text{DWRP})$$

$$W_{n+1} \leq e,$$

$$W_{n+1}-L_{n+1} \leq 0,$$

$$L_{n+1} \leq M,$$

$$L_{n+1}, X_{n+1}, O_n \geq 0, \quad n=1,2, \dots, k, \dots, 2k, \dots$$

$t=0$  for  $n < k$ ,  $t=1$  for  $k < n < 2k$  and so on, and where  $z_{(1-\alpha)}$  is the standard-ized  $100(1-\alpha)^{\text{th}}$  normal quantile.

## CONCLUSIONS

This paper provides an analytical framework for the evaluation of electricity generation and water supply for agricultural irrigation. The optimal total profit was determined by a chance-constrained linear program. We believe that through the incorporation of Recursive Least-Squares (RLS) estimates and the variance updating procedure in the model, it enables more accurate estimates of the uncertain rainfall process parameters. Further, the RLS procedure makes it easy to extend beyond the (assumed) independently, identically distributed rainfall measurements to random walk and Gauss-Markov processes. Then we could transform our CLP into a probabilistic model which is equivalent to a deterministic model. Another extension is possible through using other formulations such as stochas-

tic linear programming with recourse. In this program, the solution is obtained by making decisions in multiple stages. This modeling approach permits random variables to be incorporated in the constrained set of an LP problem. Hence, this approach is applicable to our water resource system problem. Future research is needed to test the applicability of our models under various conditions.

## REFERENCES

- Arunkumar, S., & Yeh, W. G. (1973). Probabilistic models in the design and operation of a multi-purpose reservoir system. *AVAILABLE FROM THE NATIONAL TECHNICAL INFORMATION SERVICE AS PB-232 410*, 3(25).
- Askew, A. J. (1974). Chance-constrained dynamic programming and the optimization of water resource systems. *Water Resources Research*, 10(6), 1099-1106.
- Askew, A. J. (1974). Optimum reservoir operating policies and the imposition of a reliability constraint. *Water Resources Research*, 10(1), 51-56.
- Butcher, W. S. (1971). Stochastic dynamic programming for optimum reservoir operation. *JAWRA Journal of the American Water Resources Association*, 7(1), 115-123.
- Charnes, A., & Cooper, W. W. (1963). Deterministic equivalents for optimizing and satisficing under chance constraints. *Operations research*, 11(1), 18-39.
- Geib, A. (1974). Editor, *Applied Optimal Estimation*, M.I.T. Press, Cambridge.
- Li, Y. P., Huang, G. H., & Nie, S. L. (2006). An interval-parameter multi-stage stochastic programming model for water resources management under uncertainty. *Advances in Water Resources*, 29(5), 776-789.
- Li, Z., Deng, X., Wu, F., & Hasan, S. S. (2015). Scenario analysis for water resources in response to land use change in the middle and upper reaches of the Heihe River Basin. *Sustainability*, 7(3), 3086-3108.
- Ma, Z. Z., Wang, Z. J., Xia, T., Gippel, C. J., & Speed, R. (2014). Hydrograph-Based Hydrologic Alteration Assessment and Its Application to the Yellow River. *Journal of Environmental Informatics*, 23(1).
- Maqsood, I., Huang, G. H., & Yeomans, J. S. (2005). An interval-parameter fuzzy two-stage stochastic program for water resources management under uncertainty. *European Journal of Operational Research*, 167(1), 208-225.
- Revelle, C., Joeres, E., & Kirby, W. (1969). The linear decision rule in reservoir management and design: 1, Development of the stochastic model. *Water Resources Research*, 5(4), 767-777.
- Stedinger, J. R., Sule, B. F., & Loucks, D. P. (1984). Stochastic dynamic programming models for reservoir operation optimization. *Water resources research*, 20(11), 1499-1505.
- Taylor, H. M., & Karlin, S. (1984). An introduction to stochastic modeling Academic Press. *New York*.
- Trezos, T., & Yeh, W. W. G. (1987). Use of stochastic dynamic programming for reservoir management. *Water Resources Research*, 23(6), 983-996.
- Wang, S., & Huang, G. H. (2011). Interactive two-stage stochastic fuzzy programming for water resources management. *Journal of environmental management*, 92(8), 1986-1995.
- Wang, Z., Yang, J., Deng, X., & Lan, X. (2015). Optimal water resources allocation under the constraint of land use in the Heihe River Basin of China. *Sustainability*, 7(2), 1558-1575.
- Yeh, W. W. G. (1985). Reservoir management and operations models: A state-of-the-art review. *resources research*, 21(12), 1797-1818