

Fuzzy Efficiency Decomposition in Two–Stage Systems: A new Slack-Based Measure Approach

Ziyae Berentin.M.^a, Tohidi.G.^b, Razavyan.S^{1c}, Barkhordari Ahmadi.M.^d

^a Department of Mathematics, Lahijan Branch, Islamic Azad University, Lahijan, Iran

^b Department of Mathematics, Central Tehran Branch, Islamic Azad University, Tehran, Iran

^c Department of Mathematics, South Tehran Branch, Islamic Azad University, Tehran, Iran

^d Department of Mathematics, Bandarabbas Branch, Islamic Azad University, Bandarabbas, Iran

Abstract

Data envelopment analysis (DEA) is a non-parametric tool for evaluating the relative efficiency of comparable entities referred to as Decision Making Units (DMUs). Conventional DEA models treat systems as black box and do not consider their internal structure. Network data envelopment analysis (NDEA) is a prominent method for assessing the efficiency of network systems based on radial and non-radial approaches. The special case of network systems are two-stage systems. Many real practices have two-stage structure where is divided into two processes. Conventional NDEA calculates the efficiency of these systems in presence of crisp data. But in real life applications, the observed values of data are often uncertain. In this paper, for the first time, a new non-radial approach (based on slack based measure) is introduced, which evaluates the efficiency of two-stage systems in the presence of triangular fuzzy numbers(TFNs) using α – cut technique and optimistic and pessimistic procedures. The properties of the suggested models will also be examined. Finally, a numerical example will be provided to illustrate the proposed models.

Keywords: Data Envelopment Analysis, Efficiency, Two stage system, Triangular fuzzy number, Slack Based Measure.

1. Introduction

DEA introduced by Charnes, et al. [10] is a non-parametric tool for evaluating the relative efficiency of comparable entities referred to as Decision Making Units (DMUs). The first form of DEA was called CCR model. Then, the numerous studies have been presented by extending this model. Conventional DEA models treat systems as black box and do not consider their internal structure. As discussed in many DEA papers (researches), *DMUs* may have network structure.

¹ Corresponding author.

E-mail addresses: M_ziyae@yahoo.com (M.ziyae), G.tohidi@iauctb.ac.ir (GH. Tohidi), sh_razavyan@azad.ac.ir (S. Razavyan), mahnaz_barkhordari@yahoo.com(M. Barkhordari).

Hence, new DEA studies have been done that measure the efficiency of systems with a network structure and are called NDEA models. In many applications such as banks, hospitals, etc., the internal structure of systems can be considered in the form of two stages in which the intermediate measures (produced in the first stage) are consumed by the second stage in the role of input. In recent years, much attention has been paid to evaluate the performance of these two-stage systems and their developed structures. Researchers point out several procedures for measuring the efficiency of two-stage systems based upon geometric, additive mean and SBM efficiency. Firstly, Seiford and Zhu [40] suggested models for measuring the efficiency of two-stage systems, independently. A weakness of their proposed approach is that the first and second stages may not be efficient, but the whole system may be efficient. Therefore, considering the relationship between stages in performance evaluation, a new model based on the geometric mean of stages efficiency was introduced by Kao and Hwang [25]. In fact, their proposed model calculates the efficiency of the system and the stages under the constant returns to scale (CRS), but is unable to evaluate the efficiency under the variable returns to scale (VRS). This problem was solved by Chen et al. [12] by introducing models based on the additive approach. Large number of authors focused on developed two-stage systems and have presented models to evaluate the performance of these systems. For example, the efficiency of two-stage systems in the presence of shared inputs and shared outputs by using the additive decomposition approach was calculated by Li et al. [30] (see [4, 8, 11, 15, 24]). Using slacks-based measure, a non-radial slacks-based measure (SBM) was proposed by Tone [43] calculates the efficiency of black box systems. Then, Tone and Tsutsui [44] suggested the network slacks-based measure (NSBM) model for evaluating the efficiency of systems with internal structures. Also, Ashrafi et al. [7] presented SBM models to measure the efficiency of two-stage systems. In this approach, the projected *DMUs* for inefficient DMUs are efficient. Akhther et al. [3] evaluated the efficiency of Bangladesh bank by using a network SBM model. And also, Kao [27] introduced the model for measuring the efficiency of systems with internal processes. Based on their model, the weighted average of the efficiency of processes is defined as the overall efficiency of whole system. Esfidani et al. [16] introduced a new NSBM model to measure the stages efficiency and overall efficiency of multi-period two-stage system, simultaneously (see [42, 45]).

All articles listed are formulated only when the data are accurately measured, while in practice, this is not always possible. Actually, in real environments, uncertainty often occurs in the form of fuzzy and random environments. When data is described inaccurately or stochastic, it becomes necessary to use fuzzy theory in order to represent this type of data. To handle such circumstances, many authors have developed models to evaluate the performance of systems (especially two-stage systems) in the presence of uncertain data. Jiang et al. [23] presented the new procedure to measuring the efficiency of two-stage network systems in presence of uncertain data by using uncertainty theory. The efficiency of two-stage systems with stochastic data proposed by Esfidani et al. [17]. In order to evaluate the efficiency of systems in the presence of fuzzy data, different fuzzy approaches (such as the possibility approach, the tolerance approach, the fuzzy ranking approach, the α -level approach,...) have been suggested. Lozano and Moreno [31] presented a well-known fuzzy DEA approach to measure the efficiency of two-stage serial system. Using the

principle of expansion and the α -cut technique, Kao and Liu [26] proposed FNDEA models for evaluating the performance of two-stage systems in the presence of fuzzy data. α -cut efficiencies of two-stage systems is calculated by Lozano [32]. Liu [29] suggested a procedure to rank the fuzzy efficiency of two-stage systems. Soltani et al. [41] proposed two-stage fuzzy DEA model based on fuzzy arithmetic. Also, Nabahat [35] used a collective approach to evaluate the performance of two-stage systems using the α -cut technique. Arya and Singh [6] used the α -cut procedure and presented fuzzy models to evaluate the efficiency of two-stage parallel-series systems and calculate the lower and upper bound fuzzy efficiencies of systems. Peykani et al. [37] evaluated appraisal and ranking of *DMUs* with two-stage network structure using three procedures two-stage DEA model, adjustable possibilistic programming (APP), and chance-constrained programming (CCP). And also, a new fuzzy two-stage DEA model was presented by Izadikhah [21] to measure the efficiency of 15 branches of Melli bank in Hamedan province. In recent years, many researchers have evaluated the performance of *DMUs* in the presence of fuzzy data based on Slack-Based Measure. Agarwal[2] used possibility approach and proposed a fuzzy SBM DEA model in order to measure the efficiency given fuzzy input and output data. A new Fuzzy Network SBM model was presented by Momeni et al. [36] to survey the performance of supply chain networks with forward and reverse logistics. Afzalinejad and Abbasi [1] suggested a new dynamic slacks-based DEA model that reveals all sources of inefficiencies and provide more discrimination between *DMUs*. In order to measure the cross efficiency in DEA, Kao and Liu [28] proposed a slacks-based measure model. When the input and output data are given as fuzzy sets, Arana-Jiménez et al. [5] suggested a well-known slacks-based additive inefficiency measure to survey the problem of efficiency assessment. Mahla and Agarwal[33] presented a fuzzy SBM model for measuring the efficiency of *DMUs* using credibility measure approach. (see [9, 13, 14, 18, 19, 20, 34, 39]). In the last decade, many network DEA models have been proposed to evaluate the performance of two-stage systems in the presence of fuzzy data, and most of them ignore the input, intermediate measure and output slacks, and this is not appropriate. Therefore, we will suggested fuzzy SBM model in order to measure the efficiency of two-stage systems. Among fuzzy data, we use triangular fuzzy numbers for simplicity in calculations. The proposed models can be generalized to total fuzzy data. In order to de-fuzzy, we will use the α -cut approach and solve the created interval models with optimistic and pessimistic techniques. Then we will examine the properties of the proposed models. At the end, a numerical example is presented to illustrate the proposed approaches. The paper is structures as follows:

The second section provides a review of TFNs and also the conventional SBM model. In section3, we presented the fuzzy SBM model in presence of TFNs. Then, based on the α -cut approach, the proposed model is converted to interval model. The optimistic and pessimistic procedure is applied to solve this interval model. Properties of proposed models are also discussed in this section. In Section 4, we illustrate the suggested models by using the data of 10 Mellat bank branches in Tehran. Finally, in section 5 we present our conclusions and future research directions.

2. Preliminaries

In this subsection, firstly, we reviewed the definitions of fuzzy set, fuzzy number and triangular fuzzy number and their alpha-cut sets. Also, conventional SBM DEA model of Tone [43] is presented.

2.1 Triangular Fuzzy Number (TFN)

Suppose X is a global set. A fuzzy set \tilde{A} is defined as $\tilde{A} = \{(x, \mu_{\tilde{A}}(x)) \mid x \in X\}$ where $0 < \mu_{\tilde{A}}(x) \leq 1$ shows the degree of membership of element $x \in X$ to the set $\tilde{A} \subset X$. And also, let $S(\tilde{A})$ is as $S(\tilde{A}) = \{(x \in X \mid \mu_{\tilde{A}}(x) > 0)\}$ that denote the support of \tilde{A} . The α -cut set of \tilde{A} is defined as $\tilde{A}_\alpha = \{x \in S(\tilde{A}) \mid \mu_{\tilde{A}}(x) > \alpha\}$.

Definition 2.1.1. Let $\tilde{A} \subset R$ be a fuzzy set. If the following conditions are hold, \tilde{A} is called FN:

- 1- \tilde{A} is fuzzy set convex set if the membership function is fuzzy convex set:
 $\forall x_1, x_2 \in R, \forall \lambda \in [0, 1]: \mu_{\tilde{A}}(\lambda x_1 + (1-\lambda)x_2) \geq \min\{\mu_{\tilde{A}}(x_1), \mu_{\tilde{A}}(x_2)\}$
- 2- There is at least one $x' \in R$ such that $\mu_{\tilde{A}}(x') = 1$.
- 3- The membership $\mu_{\tilde{A}}(x)$ function is semi-continuous.

Definition 2.1.2. A FN $\tilde{A} \subset R$ is a TFN with membership function $\mu_{\tilde{A}}(x)$ of the following form:

$$\mu_{\tilde{A}}(x) = \begin{cases} \frac{x - x^l}{x^m - x^l}, & x^m - x^l \leq x \leq x^m \\ \frac{x^m + x^r - x}{x^m + x^r - x^r}, & x^m \leq x \leq x^m + x^r \end{cases}$$

Here, x^m is called mean value and x^r, x^l called the right and the left spreads of membership function, respectively. We denote the TFN by $\tilde{A} = (x^l, x^m, x^r)$. Moreover, α -cut set of TFN is defined as follows that is crisp subset of R :

$$\tilde{A}_\alpha = [\tilde{A}_\alpha^L, \tilde{A}_\alpha^U] = [(x^m - x^l) + \alpha x^l, (x^m + x^r) - \alpha x^r].$$

2.2 Slacks-Based Measure (SBM) Model

In this section, we review the SBM model that was presented by Tone[43].

Consider a set of *DMUs* that indexed by DMU_j . Also, assume that each $DMU_j (j = 1, \dots, n)$ has a black box structure with inputs $x_{ij} (i = 1, \dots, m)$ and outputs $y_{rj} (r = 1, \dots, s)$. Tone proposed the following model to measure the efficiency of the DMU_o (DMU under evaluation):

$$\begin{aligned}
E_o^s = \max & \frac{1 - \frac{1}{m} \left(\sum_{i=1}^m \frac{s_i^-}{x_{io}} \right)}{1 + \frac{1}{s} \left(\sum_{r=1}^s \frac{s_r^+}{y_{ro}} \right)} \\
s.t & \sum_{j=1}^n \lambda_j x_{ij} + s_i^- = x_{io}, \quad i = 1, \dots, m \quad (1) \\
& \sum_{j=1}^n \lambda_j y_{rj} - s_r^+ = y_{ro}, \quad r = 1, \dots, s \\
& \lambda_j, s_i^-, s_r^+ \geq 0, \quad j = 1, \dots, n \quad i = 1, \dots, m \quad r = 1, \dots, s
\end{aligned}$$

In this model, s^- , s^+ , λ are respectively the input slack, output slack and intensity vector associated with $DMU_j (j=1, \dots, n)$. Also, it is assumed that $x_o > 0$, $y_o > 0$. If $x_o = 0$, term $\frac{s_i^-}{x_{io}}$

will be removed from the model (1). And also, if $y_o = 0$, term $\frac{s_r^+}{y_{ro}}$ will be substituted by a very small positive number. It is clear that the model (1) can be turned into a linear programming using Charnes-Cooper transformation.

Definition 2.2.1. DMU_o is said to be efficient if $E_o^s = 1$.

Definition 2.2.2. $E_o^s = 1$ if and only if $s_i^{-*} = 0 (i = 1, \dots, m), s_r^{+*} = 0 (r = 1, \dots, s)$.

3. Proposed Fuzzy SBM model

In this section, by introducing the structure of two-stage systems, a model for evaluating the efficiency of these systems in the presence of TFNs is introduced.

Consider a two-stage system shown in Figure1, wherein intermediate measure in stage1 is consumed by stage2. Suppose there are n $DMUs$ with two-stage structure. The input, output and intermediate measure vectors of $DMU_j (j = 1, \dots, n)$ are x_{ij}, y_{rj}, z_{dj} , respectively.




Figure1. Two-stage production system

Now, we assume that there are systems where some observations are imprecise. Among these imprecise data, we intend to use TFNs. Note that a crisp number can be thought of (considered) as a TFN. Note that in this paper, due to the simplicity of the calculation procedure, it is assumed that inputs, intermediate measures and outputs are in the form of TFNs. Also, conventional radial

models do not pay attention to slacks in evaluating the efficiency of systems, while in many cases it is necessary to identify excess inputs as well as lack of outputs, etc. Therefore, we introduce a non-radial model that solves these problems. Hence, it is assumed that all inputs, outputs and intermediate measures are TFNs. Therefore, we denote are $\tilde{x}_{ij}, \tilde{y}_{rj}, \tilde{z}_{dj}$ TFNs. It should be noted that \sim is a fuzzy symbol. The structure of $\tilde{x}_{ij}, \tilde{y}_{rj}, \tilde{z}_{dj}$ is as follows:

$$\tilde{x}_{ij} = (\tilde{x}_{ij}^l, \tilde{x}_{ij}^m, \tilde{x}_{ij}^r) , \quad \tilde{y}_{rj} = (\tilde{y}_{rj}^l, \tilde{y}_{rj}^m, \tilde{y}_{rj}^r) , \quad \tilde{z}_{dj} = (\tilde{z}_{dj}^l, \tilde{z}_{dj}^m, \tilde{z}_{dj}^r)$$

We also note that intermediate measures in the first stage have an output role and therefore should increase and in the second stage in the input role, should decrease. Hence, the flexibility of intermediate measures in modeling issues may be problematic. Therefore, to evaluate the efficiency of two-stage systems in the presence of TFNs, we introduce the following model so that it overcomes this problem:

$$\begin{aligned} \tilde{E}_o^s = \max & \frac{1 - \frac{1}{m+D} \left(\sum_{i=1}^m \frac{s_i^-}{(\tilde{x}_{io}^l, \tilde{x}_{io}^m, \tilde{x}_{io}^r)} + \sum_{d=1}^D \frac{\pi_d}{(\tilde{z}_{do}^l, \tilde{z}_{do}^m, \tilde{z}_{do}^r)} \right)}{1 + \frac{1}{s+D} \left(\sum_{r=1}^s \frac{s_r^+}{(\tilde{y}_{ro}^l, \tilde{y}_{ro}^m, \tilde{y}_{ro}^r)} + \sum_{d=1}^D \frac{s_d}{(\tilde{z}_{do}^l, \tilde{z}_{do}^m, \tilde{z}_{do}^r)} \right)} \\ \text{s.t} & \sum_{j=1}^n \lambda_j (\tilde{x}_{ij}^l, \tilde{x}_{ij}^m, \tilde{x}_{ij}^r) + s_i^- = (\tilde{x}_{io}^l, \tilde{x}_{io}^m, \tilde{x}_{io}^r), \quad i = 1, \dots, m \\ & \sum_{j=1}^n \lambda_j (\tilde{z}_{dj}^l, \tilde{z}_{dj}^m, \tilde{z}_{dj}^r) - s_d = (\tilde{z}_{do}^l, \tilde{z}_{do}^m, \tilde{z}_{do}^r), \quad d = 1, \dots, D \quad (2) \\ & \sum_{j=1}^n \lambda_j' (\tilde{z}_{dj}^l, \tilde{z}_{dj}^m, \tilde{z}_{dj}^r) + \pi_d = (\tilde{z}_{do}^l, \tilde{z}_{do}^m, \tilde{z}_{do}^r), \quad d = 1, \dots, D \\ & \sum_{j=1}^n \lambda_j' (\tilde{y}_{rj}^l, \tilde{y}_{rj}^m, \tilde{y}_{rj}^r) - s_r^+ = (\tilde{y}_{ro}^l, \tilde{y}_{ro}^m, \tilde{y}_{ro}^r), \quad r = 1, \dots, s \\ & \lambda_j, \lambda_j', s_i^-, s_d, \pi_d, s_r^+ \geq 0, \quad j = 1, \dots, n \quad i = 1, \dots, m \quad d = 1, \dots, D \quad r = 1, \dots, s \end{aligned}$$

Wherein s_i^- , s_r^+ input slack vector and output slack vector, respectively. Also, intermediate measure slacks vectors are s_d (as output for stage 1) and π_d (as input for stage 2). λ_j , λ_j' are intensity vectors for stage 1 and stage 2, respectively. Saati [38] used the concept of α -cuts and variable substitution to present an approach for solving fuzzy DEA models. Hence, we adopted this idea for calculating the fuzzy efficiency \tilde{E}_o^{s*} . Thus, we denote:

$$\begin{aligned}
(\tilde{x}_{ij})_\alpha &= [\tilde{x}_{ij}^L, \tilde{x}_{ij}^U] = [\tilde{x}_{ij}^m - \tilde{x}_{ij}^l(1-\alpha), \tilde{x}_{ij}^m + \tilde{x}_{ij}^r(1-\alpha)] \\
(\tilde{z}_{dj})_\alpha &= [\tilde{z}_{dj}^L, \tilde{z}_{dj}^U] = [\tilde{z}_{dj}^m - \tilde{z}_{dj}^l(1-\alpha), \tilde{z}_{dj}^m + \tilde{z}_{dj}^r(1-\alpha)] \\
(\tilde{y}_{rj})_\alpha &= [\tilde{y}_{rj}^L, \tilde{y}_{rj}^U] = [\tilde{y}_{rj}^m - \tilde{y}_{rj}^l(1-\alpha), \tilde{y}_{rj}^m + \tilde{y}_{rj}^r(1-\alpha)]
\end{aligned} \tag{3}$$

As the α – cuts of \tilde{x}_{ij} , \tilde{y}_{rj} , \tilde{z}_{dj} . Then, model (3) becomes:

$$\begin{aligned}
\tilde{E}_o^s &= \max \frac{1 - \frac{1}{m+D} \left(\sum_{i=1}^m \frac{s_i^-}{[\tilde{x}_{io\alpha}^L, \tilde{x}_{io\alpha}^U]} + \sum_{d=1}^D \frac{\pi_d}{[\tilde{z}_{do\alpha}^L, \tilde{z}_{do\alpha}^U]} \right)}{1 + \frac{1}{s+D} \left(\sum_{r=1}^s \frac{s_r^+}{[\tilde{y}_{ro\alpha}^L, \tilde{y}_{ro\alpha}^U]} + \sum_{d=1}^D \frac{s_d}{[\tilde{z}_{do\alpha}^L, \tilde{z}_{do\alpha}^U]} \right)} \\
s.t \quad & \sum_{j=1}^n \lambda_j [\tilde{x}_{ij\alpha}^L, \tilde{x}_{ij\alpha}^U] + s_i^- = [\tilde{x}_{io\alpha}^L, \tilde{x}_{io\alpha}^U], \quad i = 1, \dots, m \\
& \sum_{j=1}^n \lambda_j [\tilde{z}_{dj\alpha}^L, \tilde{z}_{dj\alpha}^U] - s_d = [\tilde{z}_{do\alpha}^L, \tilde{z}_{do\alpha}^U], \quad d = 1, \dots, D \\
& \sum_{j=1}^n \lambda_j [\tilde{z}_{dj\alpha}^L, \tilde{z}_{dj\alpha}^U] + \pi_d = [\tilde{z}_{do\alpha}^L, \tilde{z}_{do\alpha}^U], \quad d = 1, \dots, D \\
& \sum_{j=1}^n \lambda_j [\tilde{y}_{rj\alpha}^L, \tilde{y}_{rj\alpha}^U] - s_r^+ = [\tilde{y}_{ro\alpha}^L, \tilde{y}_{ro\alpha}^U], \quad r = 1, \dots, s \\
& \lambda_j, \lambda_j', s_i^-, s_d, \pi_d, s_r^+ \geq 0, \quad j = 1, \dots, n \quad i = 1, \dots, m \quad d = 1, \dots, D \quad r = 1, \dots, s
\end{aligned} \tag{4}$$

Given that all coefficients in this model have interval form, hence this model represents an interval model. Thus, this model cannot be solved in its current form. Therefore, we use optimistic and pessimistic approaches for evaluation of model (4) and calculate the lower and the upper bounds of the α – cut of DMU_o (i.e. $\tilde{E}_o^{s(L)*}$, $\tilde{E}_o^{s(U)*}$). Firstly, we calculate the lower bound of the efficiency. In pessimistic approach, it is assumed that DMU_o is set to its worst situation (or DMU_o has the most unfavorable conditions) and other $DMUs$ have favorable conditions (or: the best condition). In other words, stage1 of DMU_o consumes input $\tilde{x}_{io\alpha}^U$, for producing the intermediate measure $\tilde{z}_{do\alpha}^L$. And also, the other $DMUs$, consume input $\tilde{x}_{io\alpha}^L$ to produce intermediate measure $\tilde{z}_{do\alpha}^U$. And also, in stage2, input and output of DMU_o are $\tilde{z}_{do\alpha}^U$ and $\tilde{y}_{io\alpha}^L$, respectively. The other $DMUs$ also have input $\tilde{z}_{do\alpha}^L$ and output $\tilde{y}_{io\alpha}^U$. Thus, for measuring the lower bound of the efficiency (i.e. $\tilde{E}_o^{s(L)*}$), the following model is proposed:

$$\begin{aligned}
\tilde{E}_o^{s(L)} = \max & \frac{1 - \frac{1}{m+D} \left(\sum_{i=1}^m \frac{s_i^-}{\tilde{x}_{io\alpha}^U} + \sum_{d=1}^D \frac{\pi_d}{\tilde{z}_{do\alpha}^U} \right)}{1 + \frac{1}{s+D} \left(\sum_{r=1}^s \frac{s_r^+}{\tilde{y}_{ro\alpha}^L} + \sum_{d=1}^D \frac{s_d}{\tilde{z}_{do\alpha}^L} \right)} \\
s.t & \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j \tilde{x}_{ij\alpha}^L + \lambda_o \tilde{x}_{io\alpha}^U + s_i^- = \tilde{x}_{io\alpha}^U, \quad i=1, \dots, m \\
& \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j \tilde{z}_{dj\alpha}^U + \lambda_o' \tilde{z}_{do\alpha}^L - s_d = \tilde{z}_{do\alpha}^L, \quad d=1, \dots, D \\
& \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j' \tilde{z}_{dj\alpha}^L + \lambda_o \tilde{z}_{do\alpha}^U + \pi_d = \tilde{z}_{do\alpha}^U, \quad d=1, \dots, D \\
& \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j \tilde{y}_{ro\alpha}^U + \lambda_o' \tilde{y}_{ro\alpha}^L - s_r^+ = \tilde{y}_{ro\alpha}^L, \quad r=1, \dots, s \\
& \lambda_j, \lambda_j', s_i^-, s_d, \pi_d, s_r^+ \geq 0, \quad j=1, \dots, n \quad i=1, \dots, m \quad d=1, \dots, D \quad r=1, \dots, s
\end{aligned} \tag{5}$$

By using the Charnes-Cooper transformation, model (5) can be transformed into the linear model. For this purpose, we let:

$$t = \frac{1}{1 + \frac{1}{s+D} \left(\sum_{r=1}^s \frac{s_r^+}{\tilde{y}_{ro\alpha}^L} + \sum_{d=1}^D \frac{s_d}{\tilde{z}_{do\alpha}^L} \right)}$$

And set $\eta_j = t\lambda_j$, $\eta_j' = t\lambda_j'$, $\delta_i^- = ts_i^-$, $\gamma_r^+ = ts_r^+$, $\gamma_d = t\pi_d$, $\delta_d = ts_d$. Then, the model (5) converted to the following model:

$$\begin{aligned}
\tilde{E}_o^{s(L)} &= \max t - \frac{1}{m+D} \left(\sum_{i=1}^m \frac{\delta_i^-}{\tilde{x}_{io\alpha}^U} + \sum_{d=1}^D \frac{\gamma_d}{\tilde{z}_{do\alpha}^U} \right) \\
s.t \quad & t + \frac{1}{s+D} \left(\sum_{r=1}^s \frac{\gamma_r^+}{\tilde{y}_{ro\alpha}^L} + \sum_{d=1}^D \frac{\delta_d}{\tilde{z}_{do\alpha}^L} \right) = 1 \\
& \sum_{\substack{j=1 \\ j \neq o}}^n \eta_j \tilde{x}_{ij\alpha}^L + \eta_o \tilde{x}_{io\alpha}^U + \delta_i^- = t \tilde{x}_{io\alpha}^U, \quad i=1, \dots, m \\
& \sum_{\substack{j=1 \\ j \neq o}}^n \eta_j \tilde{z}_{dja}^U + \eta_o \tilde{z}_{do\alpha}^L - \delta_d = t \tilde{z}_{do\alpha}^L, \quad d=1, \dots, D \\
& \sum_{\substack{j=1 \\ j \neq o}}^n \eta_j \tilde{z}_{dja}^L + \eta_o \tilde{z}_{do\alpha}^U + \gamma_d = t \tilde{z}_{do\alpha}^U, \quad d=1, \dots, D \\
& \sum_{\substack{j=1 \\ j \neq o}}^n \eta_j \tilde{y}_{rj\alpha}^U + \eta_o \tilde{y}_{ro\alpha}^L - \gamma_r^+ = t \tilde{y}_{ro\alpha}^L, \quad r=1, \dots, s \\
& \eta_j, \eta_j^+, \delta_i^-, \delta_d, \gamma_d, \gamma_r^+ \geq 0, \quad j=1, \dots, n \quad i=1, \dots, m \quad d=1, \dots, D \quad r=1, \dots, s \\
& t > 0
\end{aligned} \tag{6}$$

Suppose $(t^{l*}, \eta_j^{l*}, \eta_j^{l+*}, \delta_i^{l-*}, \delta_d^{l*}, \gamma_d^{l*}, \gamma_r^{l+*})$ is an optimal solution of model (6). Then the optimal solution of the model (5) will be as follows:

$$\lambda_j^{l*} = \frac{\eta_j^{l*}}{t^{l*}}, \quad \lambda_j^{l+*} = \frac{\eta_j^{l+*}}{t^{l*}}, \quad s_i^{l-*} = \frac{\delta_i^{l-*}}{t^{l*}}, \quad s_r^{l+*} = \frac{\gamma_r^{l+*}}{t^{l*}}, \quad \pi_d^{l*} = \frac{\gamma_d^{l*}}{t^{l*}}, \quad s_d^{l*} = \frac{\delta_d^{l*}}{t^{l*}}$$

Therefore, the overall efficiency $(\tilde{E}_{o\alpha}^{s(L)})$ and efficiency of stages $(\tilde{E}_{o\alpha}^{I(L)}, \tilde{E}_{o\alpha}^{II(L)})$ are as follows:

$$\begin{aligned}
\tilde{E}_{o\alpha}^{s(L)} &= \frac{1 - \frac{1}{m+D} \left(\sum_{i=1}^m \frac{s_i^{l-*}}{x_{io}^U} + \sum_{d=1}^D \frac{\pi_d^{l*}}{z_{do}^U} \right)}{1 + \frac{1}{s+D} \left(\sum_{r=1}^s \frac{s_r^{l+*}}{y_{ro}^L} + \sum_{d=1}^D \frac{s_d^{l*}}{z_{do}^L} \right)} \\
E_{o\alpha}^{I(L)} &= \frac{1 - \frac{1}{m} \sum_{i=1}^m \frac{s_i^{l-*}}{x_{io}^U}}{1 + \frac{1}{D} \sum_{d=1}^D \frac{s_d^{l*}}{z_{do}^L}}, \quad E_{o\alpha}^{II(L)} = \frac{1 - \frac{1}{D} \sum_{d=1}^D \frac{\pi_d^{l*}}{z_{do}^U}}{1 + \frac{1}{s} \sum_{r=1}^s \frac{s_r^{l+*}}{y_{ro}^L}}
\end{aligned} \tag{7}$$

Definition3.1. DMU_o is lower overall efficient if and only if $\tilde{E}_{o\alpha}^{s(L)} = 1$

Definition3.2. In stage1, DMU_o is lower efficient in the lower bound if and only if $\tilde{E}_{o\alpha}^{I(L)} = 1$

Definition3.3. In stage2, DMU_o is efficient in the lower bound if and only if $\tilde{E}_{o\alpha}^{II(L)} = 1$.

Now, we consider the optimistic approach to calculate the upper bound of the efficiency. In this procedure, DMU_o has the most favorable conditions and the remaining $DMUs$ have unfavorable conditions. Therefore, $\tilde{x}_{io\alpha}^L, \tilde{z}_{do\alpha}^L$ are inputs of stage1 and stage2, respectively. And also, the output of the first stage is $\tilde{z}_{do\alpha}^U$ and the output of the second stage is $\tilde{y}_{ro\alpha}^U$. Therefore, according to the above, model (8) is proposed to calculate the upper bound of the efficiency:

$$\tilde{E}_o^{s(U)} = \max \frac{1 - \frac{1}{m+D} \left(\sum_{i=1}^m \frac{s_i^-}{\tilde{x}_{io\alpha}^L} + \sum_{d=1}^D \frac{\pi_d}{\tilde{z}_{do\alpha}^L} \right)}{1 + \frac{1}{s+D} \left(\sum_{r=1}^s \frac{s_r^+}{\tilde{y}_{ro\alpha}^U} + \sum_{d=1}^D \frac{s_d}{\tilde{z}_{do\alpha}^U} \right)}$$

$$s.t \quad \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j \tilde{x}_{ij\alpha}^U + \lambda_o \tilde{x}_{io\alpha}^L + s_i^- = \tilde{x}_{io\alpha}^L, \quad i = 1, \dots, m$$

$$\sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j \tilde{z}_{dj\alpha}^L + \lambda_o \tilde{z}_{do\alpha}^U - s_d = \tilde{z}_{do\alpha}^U, \quad d = 1, \dots, D \quad (8)$$

$$\sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j \tilde{z}_{dj\alpha}^U + \lambda_o \tilde{z}_{do\alpha}^L + \pi_d = \tilde{z}_{do\alpha}^L, \quad d = 1, \dots, D$$

$$\sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j \tilde{y}_{ro\alpha}^L + \lambda_o \tilde{y}_{ro\alpha}^U - s_r^+ = \tilde{y}_{ro\alpha}^U, \quad r = 1, \dots, s$$

$$\lambda_j, \lambda_j', s_i^-, s_d, \pi_d, s_r^+ \geq 0, \quad j = 1, \dots, n \quad i = 1, \dots, m \quad d = 1, \dots, D \quad r = 1, \dots, s$$

By using the Charnes-Cooper transformation, model (8) can be transformed into the linear model. For this purpose, we let:

$$t' = \frac{1}{1 + \frac{1}{s+D} \left(\sum_{r=1}^s \frac{s_r^+}{\tilde{y}_{ro\alpha}^U} + \sum_{d=1}^D \frac{s_d}{\tilde{z}_{do\alpha}^U} \right)}$$

And set $\eta_j = t' \lambda_j$, $\eta_j' = t' \lambda_j'$, $\delta_i^- = t' s_i^-$, $\gamma_r^+ = t' s_r^+$, $\gamma_d = t' \pi_d$, $\delta_d = t' s_d$. Then, the model (8) converted to the following model:

$$\begin{aligned}
\tilde{E}_o^{s(U)} &= \max t' - \frac{1}{m+D} \left(\sum_{i=1}^m \frac{\delta_i^-}{\tilde{x}_{io\alpha}^L} + \sum_{d=1}^D \frac{\gamma_d}{\tilde{z}_{do\alpha}^L} \right) \\
s.t. \quad & t' + \frac{1}{s+D} \left(\sum_{r=1}^s \frac{\gamma_r^+}{\tilde{y}_{ro\alpha}^U} + \sum_{d=1}^D \frac{\delta_d}{\tilde{z}_{do\alpha}^U} \right) = 1 \\
& \sum_{\substack{j=1 \\ j \neq o}}^n \eta_j \tilde{x}_{ija}^U + \eta_o \tilde{x}_{io\alpha}^L + \delta_i^- = t' \tilde{x}_{io\alpha}^L, \quad i=1, \dots, m \\
& \sum_{\substack{j=1 \\ j \neq o}}^n \eta_j \tilde{z}_{dja}^L + \eta_o \tilde{z}_{do\alpha}^U - \delta_d = t' \tilde{z}_{do\alpha}^U, \quad d=1, \dots, D \quad (9) \\
& \sum_{\substack{j=1 \\ j \neq o}}^n \eta_j \tilde{z}_{dja}^U + \eta_o \tilde{z}_{do\alpha}^L + \gamma_d = t' \tilde{z}_{do\alpha}^L, \quad d=1, \dots, D \\
& \sum_{\substack{j=1 \\ j \neq o}}^n \eta_j \tilde{y}_{rja}^L + \eta_o \tilde{y}_{ro\alpha}^U - \gamma_r^+ = t' \tilde{y}_{ro\alpha}^U, \quad r=1, \dots, s \\
& \eta_j, \eta_j^-, \delta_i^-, \delta_d, \gamma_d, \gamma_r^+ \geq 0, \quad j=1, \dots, n \quad i=1, \dots, m \quad d=1, \dots, D \quad r=1, \dots, s \\
& t' > 0
\end{aligned}$$

Suppose $(t^{u*}, \eta_j^{u*}, \eta_j'^{u*}, \delta_i^{u-*}, \delta_d^{u*}, \gamma_d^{u*}, \gamma_r^{u+*})$ is an optimal solution of model (9). Then the optimal solution of the model (8) will be as follows:

$$\lambda_j^{u*} = \frac{\eta_j^{u*}}{t^{u*}}, \quad \lambda_j'^{u*} = \frac{\eta_j'^{u*}}{t^{u*}}, \quad s_i^{u-*} = \frac{\delta_i^{u-*}}{t^{u*}}, \quad s_r^{u+*} = \frac{\gamma_r^{u+*}}{t^{u*}}, \quad \pi_d^{u*} = \frac{\gamma_d^{u*}}{t^{u*}}, \quad s_d^{u*} = \frac{\delta_d^{u*}}{t^{u*}}$$

Therefore, the overall efficiency $(\tilde{E}_{o\alpha}^{s(U)})$ and efficiency of stages $(\tilde{E}_{o\alpha}^{I(U)}, \tilde{E}_{o\alpha}^{II(U)})$ are as follows:

$$\begin{aligned}
\tilde{E}_{o\alpha}^{s(U)} &= \frac{1 - \frac{1}{m+D} \left(\sum_{i=1}^m \frac{s_i^{u-*}}{x_{io}^L} + \sum_{d=1}^D \frac{\pi_d^{u*}}{z_{do}^L} \right)}{1 + \frac{1}{s+D} \left(\sum_{r=1}^s \frac{s_r^{u+*}}{y_{ro}^U} + \sum_{d=1}^D \frac{s_d^{u*}}{z_{do}^U} \right)} \\
E_{o\alpha}^{I(U)} &= \frac{1 - \frac{1}{m} \sum_{i=1}^m \frac{s_i^{u-*}}{x_{io}^L}}{1 + \frac{1}{D} \sum_{d=1}^D \frac{s_d^{u*}}{z_{do}^U}}, \quad E_{o\alpha}^{II(U)} = \frac{1 - \frac{1}{D} \sum_{d=1}^D \frac{\pi_d^{u*}}{z_{do}^L}}{1 + \frac{1}{s} \sum_{r=1}^s \frac{s_r^{u+*}}{y_{ro}^U}} \quad (10)
\end{aligned}$$

Definition3.4. DMU_o is overall efficient in the upper bound if and only if $\tilde{E}_{o\alpha}^{s(U)} = 1$

Definition3.5. in stage 1, DMU_o is efficient in the upper bound 1 if and only if $\tilde{E}_{o\alpha}^{1(U)} = 1$

Definition3.6. in stage2, DMU_o is efficient in the upper bound if and only if $\tilde{E}_{o\alpha}^{II(U)} = 1$.

3.1. Properties of the proposed models

In this sub-section, we will investigate the properties of the suggested models.

3.1.1. Models (5) and (9) are unit invariant. Actually, if $\tilde{x}_{ij} = (\tilde{x}_{ij}^l, \tilde{x}_{ij}^m, \tilde{x}_{ij}^r)$, $\tilde{y}_{rj} = (\tilde{y}_{rj}^l, \tilde{y}_{rj}^m, \tilde{y}_{rj}^r)$, $\tilde{z}_{dj} = (\tilde{z}_{dj}^l, \tilde{z}_{dj}^m, \tilde{z}_{dj}^r)$ are replaced by $\beta_i \tilde{x}_{ij} = (\beta_i \tilde{x}_{ij}^l, \beta_i \tilde{x}_{ij}^m, \beta_i \tilde{x}_{ij}^r)$, $\omega_r \tilde{y}_{rj} = (\omega_r \tilde{y}_{rj}^l, \omega_r \tilde{y}_{rj}^m, \omega_r \tilde{y}_{rj}^r)$, $\rho_d \tilde{z}_{dj} = (\rho_d \tilde{z}_{dj}^l, \rho_d \tilde{z}_{dj}^m, \rho_d \tilde{z}_{dj}^r)$, the efficiency do not change.

Proof. Based on the constraints of the model (5):

$$\begin{aligned} \beta_i s_i^- &= \beta_i \tilde{x}_{io\alpha}^U - \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j (\beta_i \tilde{x}_{ij\alpha}^L) - \lambda_o (\beta_i \tilde{x}_{io\alpha}^U) = \beta_i (\tilde{x}_{io\alpha}^U - \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j \tilde{x}_{ij\alpha}^L - \lambda_o \tilde{x}_{io\alpha}^U), & i=1, \dots, m \\ \rho_d s_d &= \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j (\rho_d \tilde{z}_{dj\alpha}^U) + \lambda_o' (\rho_d \tilde{z}_{do\alpha}^L) - (\rho_d \tilde{z}_{do\alpha}^L) = \rho_d (\sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j \tilde{z}_{dj\alpha}^U + \lambda_o' \tilde{z}_{do\alpha}^L - \tilde{z}_{do\alpha}^L), & d=1, \dots, D \\ \rho_d \pi_d &= \rho_d \tilde{z}_{do\alpha}^U - \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j' (\rho_d \tilde{z}_{dj\alpha}^L) - \lambda_o' (\rho_d \tilde{z}_{do\alpha}^U) = \rho_d (\tilde{z}_{do\alpha}^U - \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j' \tilde{z}_{dj\alpha}^L - \lambda_o' \tilde{z}_{do\alpha}^U), & d=1, \dots, D \\ \omega_r s_r^+ &= \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j' (\omega_r \tilde{y}_{ro\alpha}^U) + \lambda_o' (\omega_r \tilde{y}_{ro\alpha}^L) - (\omega_r \tilde{y}_{ro\alpha}^L) = \omega_r (\sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j' \tilde{y}_{ro\alpha}^U + \lambda_o' \tilde{y}_{ro\alpha}^L - \tilde{y}_{ro\alpha}^L), & r=1, \dots, s \end{aligned}$$

Hence,

$$\frac{\beta_i s_i^-}{\beta_i \tilde{x}_{io\alpha}^U} = \frac{s_i^-}{\tilde{x}_{io\alpha}^U}, \quad \frac{\rho_d \pi_d}{\rho_d \tilde{z}_{do\alpha}^U} = \frac{\pi_d}{\tilde{z}_{do\alpha}^U}, \quad \frac{\omega_r s_r^+}{\omega_r \tilde{y}_{ro\alpha}^L} = \frac{s_r^+}{\tilde{y}_{ro\alpha}^L}, \quad \frac{\rho_d s_d}{\rho_d \tilde{z}_{do\alpha}^L} = \frac{s_d}{\tilde{z}_{do\alpha}^L}$$

It is clear that the efficiency of whole system and stages will not change. The similar proof for the model (9) is hold and the proof is complete.

3.1.2. For each DMU_o : the upper bounds of the efficiency of systems and stages are in range

$$(0,1]. \text{ (i.e. } 0 < \tilde{E}_{o\alpha}^{s(L)} \leq 1, 0 < \tilde{E}_{o\alpha}^{1(L)} \leq 1, 0 < \tilde{E}_{o\alpha}^{II(L)} \leq 1).$$

Proof. According to the constraints of the model (5): $\frac{s_i^-}{\tilde{x}_{io\alpha}^U} \leq 1$, $\frac{\pi_d}{\tilde{z}_{do\alpha}^U} \leq 1$

Hence, $\sum_{i=1}^m \frac{s_i^-}{\tilde{x}_{io\alpha}^U} + \sum_{d=1}^D \frac{\pi_d}{\tilde{z}_{do\alpha}^U} \leq m + D$. Then, given that

$$1 + \frac{1}{s + D} \left(\sum_{r=1}^s \frac{s_r^+}{\tilde{y}_{ro\alpha}^L} + \sum_{d=1}^D \frac{s_d}{\tilde{z}_{do\alpha}^L} \right) \geq 1 \text{ and } 0 < 1 - \frac{1}{m + D} \left(\sum_{i=1}^m \frac{s_i^-}{\tilde{x}_{io\alpha}^U} + \sum_{d=1}^D \frac{\pi_d}{\tilde{z}_{do\alpha}^U} \right) \leq 1$$

It results that $0 < \tilde{E}_{o\alpha}^{s(L)} \leq 1$. The other efficiencies are proved similarly.

3.1.3. For each DMU_o : the upper bounds of the efficiency of systems and stages are in range $(0, 1]$. (i.e. $0 < \tilde{E}_{o\alpha}^{s(U)} \leq 1$, $0 < \tilde{E}_{o\alpha}^{l(U)} \leq 1$, $0 < \tilde{E}_{o\alpha}^{II(U)} \leq 1$).

Proof. Similar to the proof (3.1.2).

3.1.5. Suppose $(t^{l*}, \lambda_j^{l*}, \lambda_j^{l'*}, s_i^{l-*}, s_r^{l+*}, \pi_d^{l*}, s_d^{l*})$ is an optimal solution of the model (5). In this case, $\tilde{E}_{o\alpha}^{s(L)} = 1$ if and only if $s_i^{l-*} = 0$, $s_r^{l+*} = 0$, $\pi_d^{l*} = 0$, $s_d^{l*} = 0$. (A similar situation can be written for the efficiency of the stages).

Proof. If $s_i^{l-*} = 0$, $s_r^{l+*} = 0$, $\pi_d^{l*} = 0$, $s_d^{l*} = 0$, it is obvious that $\tilde{E}_{o\alpha}^{s(L)} = 1$. Conversely, if $\tilde{E}_{o\alpha}^{s(L)} = 1$, we have:

$$1 - \frac{1}{m + D} \left(\sum_{i=1}^m \frac{s_i^{u-*}}{\tilde{x}_{io}^L} + \sum_{d=1}^D \frac{\pi_d^{u*}}{\tilde{z}_{do}^L} \right) = 1 + \frac{1}{s + D} \left(\sum_{r=1}^s \frac{s_r^{u+*}}{\tilde{y}_{ro}^U} + \sum_{d=1}^D \frac{s_d^{u*}}{\tilde{z}_{do}^U} \right)$$

This give the result that $s_i^{l-*} = 0$, $s_r^{l+*} = 0$, $\pi_d^{l*} = 0$, $s_d^{l*} = 0$.

3.1.6. Suppose $(t^{u*}, \lambda_j^{u*}, \lambda_j^{u'*}, s_i^{u-*}, s_r^{u+*}, \pi_d^{u*}, s_d^{u*})$ is an optimal solution of the model (5). In this case, $\tilde{E}_{o\alpha}^{s(U)} = 1$ if and only if $s_i^{u-*} = 0$, $s_r^{u+*} = 0$, $\pi_d^{u*} = 0$, $s_d^{u*} = 0$. (A similar situation can be written for the efficiency of the stages).

Proof. Similar to the proof (3.1.5).

3.1.7. $\tilde{E}_{o\alpha}^{s(L)} = 1$ if and only if $\tilde{E}_{o\alpha}^{l(L)} = 1$, $\tilde{E}_{o\alpha}^{II(L)} = 1$.

Proof. If $\tilde{E}_{\alpha\alpha}^{s(L)} = 1$, then $s_i^{l-*} = 0$, $s_r^{l+*} = 0$, $\pi_d^{l*} = 0$, $s_d^{l*} = 0$. in this case we have $\tilde{E}_{\alpha\alpha}^{l(L)} = 1$, $\tilde{E}_{\alpha\alpha}^{II(L)} = 1$. Conversely, if $\tilde{E}_{\alpha\alpha}^{l(L)} = 1$, $\tilde{E}_{\alpha\alpha}^{II(L)} = 1$, it is obvious that $\tilde{E}_{\alpha\alpha}^{s(L)} = 1$.

3.1.8. $\tilde{E}_{\alpha\alpha}^{s(U)} = 1$ if and only if $\tilde{E}_{\alpha\alpha}^{I(U)} = 1$, $\tilde{E}_{\alpha\alpha}^{II(U)} = 1$.

Proof. Similar to the proof (3.1.7).

3.1.9. Let $\hat{x}_{ij} \in [\tilde{x}_{ij\alpha}^L, \tilde{x}_{ij\alpha}^U]$, $\hat{z}_{dj} \in [\tilde{z}_{dj\alpha}^L, \tilde{z}_{dj\alpha}^U]$, $\hat{y}_{rj} \in [\tilde{y}_{rj\alpha}^L, \tilde{y}_{rj\alpha}^U]$. And suppose $(\lambda_j^*, \lambda_j^*, s_i^{-*}, s_d^*, \pi_d^*, s_r^{+*})$ is an optimal solution of the model (4). Hence, it can be concluding that: “each optimal solution of the model (4) is a feasible solution of the model (5)”.

Proof. Given that $\tilde{x}_{ij\alpha}^L \leq \hat{x}_{ij} \leq \tilde{x}_{ij\alpha}^U$, $\tilde{z}_{dj\alpha}^L \leq \hat{z}_{dj} \leq \tilde{z}_{dj\alpha}^U$, $\tilde{y}_{rj\alpha}^L \leq \hat{y}_{rj} \leq \tilde{y}_{rj\alpha}^U$, using rewriting the constraints of model the model(4), we have:

$$\begin{aligned} \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j^* \tilde{x}_{ij\alpha}^L &\leq \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j^* x_{ij} \leq (\lambda_o^* + 1)x_{io} \leq (\lambda_o^* + 1)\tilde{x}_{io\alpha}^U, & i = 1, \dots, m \\ \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j^* \tilde{z}_{dj\alpha}^U &\geq \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j^* z_{dj} \geq (\lambda_o^* - 1)z_{do} \geq (\lambda_o^* - 1)\tilde{z}_{do\alpha}^L, & d = 1, \dots, D \\ \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j^{r*} \tilde{z}_{dj\alpha}^L &\leq \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j^{r*} z_{dj} \leq (\lambda_o^{r*} + 1)z_{do} \leq (\lambda_o^{r*} + 1)\tilde{z}_{do\alpha}^U, & d = 1, \dots, D \\ \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j^{r*} \tilde{y}_{ro\alpha}^U &\geq \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j^{r*} y_{rj} \geq (\lambda_o^{r*} - 1)y_{ro} \geq (\lambda_o^{r*} - 1)\tilde{y}_{io\alpha}^L, & r = 1, \dots, s \end{aligned}$$

Therefore:

$$\begin{aligned} \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j^* \tilde{x}_{ij\alpha}^L &\leq (\lambda_o^* + 1)\tilde{x}_{io\alpha}^U, & i = 1, \dots, m \\ \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j^* \tilde{z}_{dj\alpha}^U &\geq (\lambda_o^* - 1)\tilde{z}_{do\alpha}^L, & d = 1, \dots, D \\ \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j^{r*} \tilde{z}_{dj\alpha}^L &\leq (\lambda_o^{r*} + 1)\tilde{z}_{do\alpha}^U, & d = 1, \dots, D \\ \sum_{\substack{j=1 \\ j \neq o}}^n \lambda_j^{r*} \tilde{y}_{ro\alpha}^U &\geq (\lambda_o^{r*} - 1)\tilde{y}_{io\alpha}^L, & r = 1, \dots, s \end{aligned}$$

And so, the proof is complete.

3.1.10. Let $\hat{x}_{ij} \in [\tilde{x}_{ij}^L, \tilde{x}_{ij}^U]$, $\hat{z}_{dj} \in [\tilde{z}_{dj}^L, \tilde{z}_{dj}^U]$, $\hat{y}_{rj} \in [\tilde{y}_{rj}^L, \tilde{y}_{rj}^U]$. And suppose $(\lambda_j^*, \lambda_j^{+*}, s_i^-, s_d^*, \pi_d^*, s_r^{+*})$ is an optimal solution of the model (4). Hence, it can be concluding that: each optimal solution of the model (8) is a feasible solution of the model (4).

Proof. Similar to the proof (3.1.9).

4. Case study

To illustrate the proposed models in this paper, we use the data of 10 Mellat bank branches in Tehran for the year 2013[16]. Note that the proposed models (5), (8) calculate the lower and the upper the bound of the efficiency, respectively. In recently years, evaluating the efficiency of bank branches is an important topic. Each bank branch is composed of two-stage. Actually, each bank branch is considered as a DMU with a two-stage structure. "Personal score", "Paid profit" are inputs of stage1. Also, we use two intermediate measures" Total of four deposits", "Other resources" and 4 outputs "Facilities", "Received handling fee", "Earned profit", "Deferred claims". Note that undesirable output "Deferred claims" is considered as its inverse. It must be noted that each real number x can be considered as a TFN (i.e. (x^l, x^m, x^r)). Hence, we consider data have TFN structure. Thus, we firstly, calculate the α - cut intervals for inputs and outputs and intermediate measures. For TFN x , the α - cut interval is $[x^m - x^l(1-\alpha), x^m + x^r(1-\alpha)]$. Suppose that $\alpha = 0.25$. For DMU_2 , the α -cut intervals of personal score and paid profit are [6.07, 8.445] and [523081701, 5233176187], respectively. These intervals are calculated following similarly for other $DMUs$.

Finally, by applying these intervals to models 5 and 8, the results are obtained.

DMU	$[\tilde{E}_o^{s(L)}, \tilde{E}_o^{s(U)}]$	$[\tilde{E}_o^{I(L)}, \tilde{E}_o^{I(U)}]$	$[\tilde{E}_o^{II(L)}, \tilde{E}_o^{II(U)}]$
1	[0.5000,0.6326]	[1,1]	[0.3960,0.5344]
2	[0.1116,0.1523]	[0.0125,0.3460]	[0.7081,1]
3	[0.1956,0.4876]	[1,1]	[0.2960,0.3788]
4	[0.1650,0.3242]	[0.0260,0.1340]	[0.1138,0.2579]
5	[0.2520,0.2652]	[0.0852,0.1248]	[0.2197,0.2688]
6	[0.0523,0.1547]	[0.1037,0.2690]	[0.1329,0.6987]
7	[0.2610,0.6123]	[0.1420,0.5250]	[0.1120,0.5642]

8	[0.1780,0.2472]	[0.1892,0.3283]	[0.2639,0.5176]
9	[0.1917,0.2587]	[0.4363,0.4578]	[0.1735,0.3528]
10	[0.2361,0.7230]	[0.5856,0.6913]	[0.1842,0.4549]

Table 1. *The upper and the lower bound of the efficiencies*

Now, we illustrate these obtained results. The second to fourth columns report intervals of the overall efficiency and the efficiency of stages, respectively. Based on this table, all of *DMUs* are inefficient in whole system. DMU_1 and DMU_3 are the upper (and the lower) efficient in stage 1. In stage 2, DMU_2 is efficient at the upper bound. In the lower bound of the efficiencies, between inefficient *DMUs* of whole system and stages 1, 2, DMU_1 , DMU_{10} and DMU_2 have the best efficiency with scores 0.5856, 0.7081 and 0.5000, respectively. Also, the lowest efficiency of the lower bound belongs to DMU_6 , DMU_2 and DMU_7 , respectively. In upper bound, DMU_{10} has the highest efficiency in whole system and stage1. And also, DMU_5 has the worst efficiency in the stages 1 and 2 with scores 0.1248 and 0.2688, respectively. A similar interpretation can be written for other *DMUs*.

5. Conclusion

DEA is a useful technique for evaluating the efficiency of systems. Conventional DEA consider *DMUs* as a black box. But in practice many systems may have a network structure and this structure of these systems is ignored in evaluating the performance. Hence, to solve this problem, NDEA models are proposed to measure the efficiency of these systems. Note that in practice, many *DMUs* (such as banks, etc.) can be considered as a two-stage system. Thus, two-stage systems are very importance among network systems. So far, many models are introduced to calculate the efficiency of this systems in presence of certain and uncertain data. In many manufacturing processes, uncertain data can be expressed by FN. Hence, in this paper, we focused on TFNs and presented a novel approach based on the non-redial models to evaluate the efficiency of two-stage systems in presence of TFNs. Actually, we considered all fuzzy inputs, intermediate measures and outputs are TFNs and suggested a non-redial model to evaluate the efficiency. For solving the proposed model, we used α - cut approach and calculated α - cut intervals of the inputs, intermediate measures and outputs. By applying these intervals to the proposed model, an interval model was obtained. Then, an optimistic and pessimistic procedure was used to solve the obtained interval model. Finally, some of the properties of the proposed model was described. It must be noted that we have shown that the whole system is efficient if and only if its stages are efficient. For future study, this technique can be extend the fuzzy DEA models to the multi-period slacks-based DEA models.

References

- [1] Afzalinejad M, Abbasi Z, 2019 A slacks-based model for dynamic data envelopment analysis. *Journal of Industrial & Management Optimization*, 15, 275-291. doi: 10.3934/jimo.2018043.
- [2] Agarwal S, 2014. Efficiency Measure by Fuzzy Data Envelopment Analysis-Model. *Fuzzy Inf. Eng*, 6, 59-70.
- [3] Akther S, Fukuyama H, Weber W.L, 2013 Estimating two-stage network Slacks-based inefficiency: an application to Bangladesh banking. *Omega* 41, 88-96.
- [4] Amirteimoori A, Despotis K, Kordrostami S, Azizi H, 2016 Additive models for network data envelopment analysis in the presence of shared resources. *Transportation Research Part D: Transport and Environment*, 48, 411-424.
- [5] Arana-Jiménez M, Sánchez-Gil C, Lozano S, 2020 A fuzzy DEA slacks-based approach. *Journal of Computational and Applied Mathematics*, <https://doi.org/10.1016/j.cam.2020.113180>.
- [6] Arya A, Singh S, 2021 Development of two-stage parallel-series system with fuzzy data: A fuzzy DEA approach. *Soft Computing*, <https://doi.org/10.1007/s00500-020-05374-w>.
- [7] Ashrafi A, Jaafar A.B, Lee L.S, Abu Bakar M.R, 2011 A slacks-based measure of efficiency in two-stage data envelopment analysis. *Int. J. Math. Anal.* 5, 1435-1444.
- [8] Aviles-Sacoto S, Cook W.D, Imanirad R, Zhu J, 2015 Two-stage network DEA: when intermediate measures can be treated as outputs from the second stage. *Journal of the Operational Research Society*, 66(11), 1868–1877.
- [9] Azadi M, Jafarian M, FarzipoorSaen R, Mirhedayatian S.M, 2015 A new fuzzy DEA model for evaluation of efficiency and effectiveness of supplier sustainable supply chain management context, *Computers & Operations Research*, 54, 274–285.
- [10] Charnes A, Cooper W.W, Rhodes E, 1978 Measuring the efficiency of decision making units. *European Journal of Operational Research*, 2, 429 - 444.
- [11] Cook W.D, Zhu J, Bi G, Yang F, 2010 Network DEA: additive efficiency decomposition. *European Journal of Operational Research*, 207, 1122–1129.
- [12] Chen Y, Cook W.D, Li N, Zhu J, 2009 Additive efficiency decomposition in two-stage DEA. *European Journal of Operational Research*, 196, 1170–1176.
- [13] Ebrahimnejad A, Amani N, 2020 Fuzzy data envelopment analysis in the presence of undesirable outputs with ideal points. *Complex & Intelligent Systems*, 7, 379–400.

- [14] Ebrahimzadeh Shermeh H, Najafi S.E, Alavidoost M.H, 2016 A novel fuzzy network SBM model for data envelopment analysis: A case study in Iran regional power companies. *Energy* 112, 686e697.
- [15] Esfidani S, Hosseinzadeh Lotfi F, Razavyan S.H, Ebrahimnejad A, 2018 Efficiency changes index in the network data envelopment analysis with non-radial model. *Asian-European Journal of Mathematics*, 13(1).
- [16] Esfidani S, Hosseinzadeh Lotfi F, Razavyan S, Ebrahimnejad A, 2019 A Slacks-based measure approach for efficiency decomposition in multi-period two-stage systems. *RAIRO-Operation Research*, doi: <https://doi.org/10.1051/ro/2019113>.
- [17] Esfidani S, Hosseinzadeh Lotfi F, Razavyan S, Ebrahimnejad A, 2020 Efficiency of two-stage systems in stochastic DEA. *Journal of Mathematical Extension*.
- [18] Ghelej Beigi Z, Gholami K, 2014 Allocating the Fuzzy Resources to Two-Stage Systems. *Journal of Soft Computing and Applications*, 1-11.
- [19] Hatami-Marbini A, Saati M.S, Tavana, M, 2011 Data Envelopment Analysis with Fuzzy Parameters: An Interactive Approach. *International Journal of Operations Research and Information Systems*, 2(3), 39-53.
- [20] Hatami-Marbini, A, Emrouznejad A, Tavana M, 2011 A taxonomy and review of the fuzzy data envelopment analysis literature: Two decades in the making. *Eur J Oper Res*, 214, 457-472.
- [21] Izadikhah M, 2021 Modelling Bank Performance: A Novel Fuzzy Two-Stage DEA Approach. *Fuzzy Information and Engineering*, 11(2).149-174.
- [22] Izadikhah M, Tavana M, Caprio D.D, Santos-Arteaga F.J, 2018 A novel two-stage DEA production model with freely distributed initial inputs and shared intermediate outputs. *Expert Systems with Applications*, 99(1): 213-230.
- [23] Jiang B, Chen H, Li J, Lio W, 2020 The uncertain two-stage network DEA models. *Soft Computing*. <https://doi.org/10.1007/s00500-020-05157-3>.
- [24] Jianfeng M.A, 2015 A two-stage DEA model considering shared inputs and free intermediate measures. *Expert Systems with Applications* 42:4339–4347.
- [25] Kao C, Hwang S.N, 2008 Efficiency decomposition in two-stage data envelopment analysis: An application to non-life insurance companies in Taiwan. *Eur J Oper Res*, 185: 418–429.
- [26] Kao C, Liu S.T, 2011 Efficiencies of two-stage systems with fuzzy data. *Fuzzy Sets and Systems*, 176, 20-35.

- [27]. Kao C, 2014 Efficiency decomposition in network data envelopment analysis with slacks based measures. *Omega* 45, 1-6.
- [28] Kao C, Liu S.T, 2020 A slacks-based measure model for calculating cross efficiency in data envelopment analysis, *Omega*.doi:<https://doi.org/10.1016/j.omega.2020.102192>.
- [29] Liu S.T 2014 Fuzzy efficiency ranking in fuzzy two-stage data envelopment analysis. *Optimization Letters*, 8(2).
- [30] Li L, Dai Q, Huang H, Wang S, 2016 Efficiency decomposition with shared inputs and outputs in two – stage DEA. *Journal of Systems Science and Systems Engineering*, 25(1), 23-38.
- [31] Lozano S, Moreno P, 2013 A DEA model for two-stage systems with Fuzzy data. *IEEE International Conference on Fuzzy Systems (FUZZ-IEEE)*, 1-6, doi: 10.1109/FUZZ-IEEE.2013.6622307.
- [32] Lozano S, 2014 Process efficiency of two-stage systems with fuzzy data, *Fuzzy Sets and Systems*.243, 36-49.
- [33] Mahla D, Agarwal S,2021 A Credibility Approach on Fuzzy Slacks Based Measure (SBM) DEA Model. *Iranian Journal of Fuzzy Systems*. MSC: 90C70.
- [34] MahlaD, Agarwal S, Mathur T, 2021 A novel fuzzy non-radial data envelopment analysis: an Application in transportation. *RAIRO-Oper. Res.* 55, 2189-2202, <https://doi.org/10.1051/ro/2021097>.
- [35] Nabahat M, 2015 Two-stage DEA with Fuzzy Data. *International Journal of Applied Operational Research*, 5(1), 51-61.
- [36] Momeni E,Tavana M, Mirzagoltabard H, Mirhedayatiane S.M, 2014 A new fuzzy network slacks-based DEA model for evaluating performance of supply chains with reverse logistics. *Journal of Intelligent & Fuzzy Systems* 27, 793–804.
- [37] Peykani, Mohammadi E, Ali Emrouznejad A,2021 An adjustable fuzzy chance-constrained network DEA approach with application to ranking investment firms. *Expert Systems with Applications*, 166, 113938.
- [38] Saati S, Memariani A, 2002 Efficiency Analysis and Ranking of DMUs with Fuzzy Data. *Fuzzy Optimization and Decision Making*, 1, 255– 267.
- [39] Saati S, Memariani A, 2004 SBM model with fuzzy input-output level in DEA. *Australian Journal of Basic and Applied Sciences*, 3(2), 352-357.
- [40] Seiford L.M, Zhu J, 1999 Profitability and marketability of the top 55 US commercial Banks. *Manag. Sci*, 45, 1270–1288.

- [41] Soltani M.R, Edalatpanah S.A, Movahhedi Sobhani F, Najafi S.E, 2020 A Novel Two-Stage DEA Model in Fuzzy Environment: Application to Industrial Workshops Performance Measurement. *International Journal of Computational Intelligence Systems*, 13(1), 1134–1152.
- [42] Tali A.M, Padi T.R, Dar Q.F, 2016 Slack- based Measures of Efficiency in Two-stage Process: An Approach Based on Data Envelopment Analysis with Double Frontiers. *Int. J Latest Trends Fin. Eco. Sc*, 6(3).
- [43] Tone K, 2001 Theory and methodology a slacks-based measure of efficiency in data envelopment analysis. *Eur. J. Oper. Res.* 130, 498-509.
- [44] Tone K, Tsutsui M, 2009 Network DEA: a slacks-based measure approach. *Eur. J. Oper. Res.* 197,243-252.
- [45] Zhu Y, Yongjun Li Y, Liang L, 2017 A variation of two-stage SBM with leader–follower structure: an application to Chinese commercial banks. *Journal of the Operational Research Society*. doi:10.1057/s41274-017-0262-z.