

Nonlinear Vibration Analysis of a Cantilever Beam with Nonlinear Geometric

M. Mashinchi Joubari^{1*}, H. Javaniyan Jouybari², D. D. Ganji³

Received: 10 June 2013; Accepted: 30 September 2013

Abstract: Analyzing the nonlinear vibration of beams is one of the important issues in structural engineering. According to this, an impressive analytical method which is called modified iteration perturbation method (MIPM) is used to obtain the behavior and frequency of a cantilever beam with geometric nonlinear. This new method is combined by the Mickens and iteration methods. Moreover, this method does not require small parameter in the equation which is difficult to be found for nonlinear oscillation. The accuracy of the solution that is obtained by the use of MIPM has been shown graphically and compared with exact solution. Comparison shows that good adaptation is obtained and MIPM as a powerful method for solving the vibrational behavior of structures analytically.

Keywords: Nonlinear Vibration, Cantilever Beam, Nonlinearity Geometric, Modified Iteration Perturbation Method, Total Loss Coefficient

1. Introduction

Investigation the dynamic response of the systems such as air plane wings is vital aspect in mechanical engineering. Because the skin panel of these structures may experience serious structural problems such as thermal buckling or panel flutters, studying about them should be very carefully without missing any parameter. In this paper, the air plane wings are assumed as a cantilever beam with nonlinear geometry.

Recently, researchers have analyzed free vibration of nonlinear beams. Rehfield [1] proposed an approximate method for nonlinear vibration problems with material nonlinear effects for various boundary conditions. Sathyamoorthy [2] developed the work on finite element method for nonlinear beams

under static and dynamic loads and classical methods for the analysis of beams with material, geometry and other types of nonlinearities. Klein [3] used finite element approach and Rayleigh-Ritz for analyzing the vibration of the tapered beams. A dynamic discretization technique was applied to calculate the natural frequencies of a non-rotating double tapered beam based on both the Euler-Bernoulli and Timoshenko Beam Theories by Downs [4]. Sato [5], improved the Ritz method to study a linearly tapered beam with ends restrained elastically against rotation and subjected to an axial force. Lau [6], used the exact method for studying on the free vibration of tapered beam with end mass.

The Green's function method in Laplace transform domain was used to study the vi-

1*. Corresponding Author: M. Sc., Dept. of Mechanical Engineering, Babol University of Technology, Babol, Iran (mmmjouybari@gmail.com)

2. Young Researchers and Elite Club, South Tehran Branch, Islamic Azad University, Tehran, Iran (hamidjavaniyan@gmail.com)

3. Assistant Professor, Department of Mechanical Engineering, Babol University of Technology, Babol, Iran (mirgang@nit.ac.ir)

bration of general elastically restrained tapered beams by Lee et al [7]. It obtain the approximate fundamental solution by using a number of stepped beams to represent the tapered beam. Kopmaz et al. [8] considered different approaches to describing the relationship between the bending moment and curvature of an Euler-Bernoulli beam undergoing a large deformation. Then, in the case of a cantilevered beam subjected to a single moment at its free end, the difference between the linear and the nonlinear theories based on both the mathematical curvature and the physical curvature was shown.

In this paper, the vibration equation of a cantilever beam is solved by using of modified iteration perturbation method. It shows that the solution is quickly convergent and doesn't need to complicated calculations. Also, the equation derived from this problem is nonlinear. Usually, solving equations with nonlinear components have been one of the most time-consuming and difficult affairs among engineers. In recent years, much attention has been done to new approximate methods for solving nonlinear oscillation [9, 10]. Some of them are, frequency amplitude formulation [11], variational iteration [12, 13], iteration perturbation method [14-16], homotopy-perturbation [17, 18], parame- trized-perturbation [19], max-min [20, 21, 22], newton harmonic balance method [23, 24], differential transformation method [25], energy balance [26, 27] and etc.

2. Materials and methods

2.1. Basic idea of modified iteration perturbation method

The modified iteration perturbation method (MIPM) is composed of the Mickens and Iteration methods. For the first time, it

was used by Marinca and Herisanu [28].

By considering the following equation as the general nonlinear oscillation:

$$\ddot{u} + \omega^2 u = f(u, \dot{u}, \ddot{u}), \quad u(0) = A, \quad \dot{u}(0) = 0 \quad (1)$$

Eq. (1) is rewritten in the following from:

$$\ddot{u} + \Omega^2 u = u(\Omega^2 - \omega^2 + \frac{f(u, \dot{u}, \ddot{u})}{u}) := ug(u, \dot{u}, \ddot{u}), \quad (2)$$

where Ω is a priori unknown frequency of the periodic solution, $u(t)$ being sought. The proposed iteration scheme is:

$$\begin{aligned} \ddot{u}_{n+1} + \Omega^2 u_{n+1} = & u_{n-1} [g(u_{n-1}, \dot{u}_{n-1}, \ddot{u}_{n-1}) + \\ & g_u(u_{n-1}, \dot{u}_{n-1}, \ddot{u}_{n-1})(u_n - u_{n-1}) + \dots \\ & g_{\dot{u}}(u_{n-1}, \dot{u}_{n-1}, \ddot{u}_{n-1})(\dot{u}_n - \dot{u}_{n-1}) + \\ & g_{\ddot{u}}(u_{n-1}, \dot{u}_{n-1}, \ddot{u}_{n-1})(\ddot{u}_n - \ddot{u}_{n-1})], \quad n = 0, 1, 2, \end{aligned} \quad (3)$$

where the inputs of starting functions are (Lim and Wu, 2002):

$$u_{-1}(t) = u_0(t) = A \cos \Omega t. \quad (4)$$

It is further required that for each n , the solution to Eq. (3) is to satisfy the initial conditions.

$$u_n(0) = A, \quad \dot{u}_n(0) = 0. \quad n = 1, 2, 3, \dots \quad (5)$$

Note that for given $u_{n-1}(t)$ and $u_n(t)$, Eq. (3) is second order inhomogeneous differential equation for $u_{n+1}(t)$. The right hand side of Eq. (3) can be expand into the following Fourier series:

$$\begin{aligned} & u_{n-1} [g(u_{n-1}, \dot{u}_{n-1}, \ddot{u}_{n-1}) + \\ & g_u(u_{n-1}, \dot{u}_{n-1}, \ddot{u}_{n-1})(u_n - u_{n-1}) + \dots \\ & g_{\dot{u}}(u_{n-1}, \dot{u}_{n-1}, \ddot{u}_{n-1})(\dot{u}_n - \dot{u}_{n-1}) + \\ & g_{\ddot{u}}(u_{n-1}, \dot{u}_{n-1}, \ddot{u}_{n-1})(\ddot{u}_n - \ddot{u}_{n-1})] = \\ & a_1(A, \Omega, \omega) \cos \Omega t + \dots \quad (6) \\ & \sum_{n=2}^N a_n(A, \Omega, \omega) \cos n \Omega t + b_1(A, \Omega, \omega) \sin \Omega t + \\ & \sum_{n=2}^N b_n(A, \Omega, \omega) \sin n \Omega t, \end{aligned}$$

where the coefficients $a_n(A, \Omega, \omega)$ and $b_n(A, \Omega, \omega)$ are known, and the integer N depends upon the function $g(u, \dot{u}, \ddot{u})$ on the right hand side of Eq. (2) in Eq. (6), the requirement of no secular term needs.

$$a_1(A, \Omega, \omega) = 0, \quad b_1(A, \Omega, \omega) = 0. \quad (7)$$

The solution of Eq. (3) with the initial conditions of Eq. (5) is given by:

$$u_{n+1}(t) = A \cos \Omega t - \sum_{n=2}^N \frac{a_n(A, \Omega, \omega)}{(n^2 - 1)\Omega^2} (\cos n\Omega t - \cos \Omega t) - \sum_{n=2}^N \frac{b_n(A, \Omega, \omega)}{(n^2 - 1)\Omega^2} (\sin n\Omega t - \sin \Omega t). \quad (8)$$

Eq. (7) allows the determination of the frequency Ω as a function of A and ω . This procedure can be performed to any desired iteration step n. As in the following example will be shown, an excellent approximate analytical representation to the exact solution is obtained. This representation valid for small values as well as large values of the oscillation amplitude.

2.2. Application of the modified iteration perturbation method

The vibration equation of a cantilever beam with nonlinear geometry can be assumed as:

$$\ddot{u} + \varepsilon_1(u^2\ddot{u} + u\dot{u}^2) + u + \varepsilon_2u^3 = 0 \quad (9)$$

where initial conditions are $u(0) = A, \dot{u}(0) = 0$.

Eq. (9) is rewritten as follows:

$$\ddot{u} + \Omega^2u = u(\Omega^2 - 1 - \varepsilon_1(u\ddot{u} + \dot{u}^2) - \varepsilon_2u^2) \quad (10)$$

The inputs of the starting function are $u_{-1}(t) = u_0(t) = A \cos \Omega t$ and

$$g(u, \dot{u}, \ddot{u}, t) = \Omega^2 - 1 - \varepsilon_1(u\ddot{u} + \dot{u}^2) - \varepsilon_2u^2.$$

So, the first iteration is given by the equation

$$\ddot{u}_1 + \Omega^2u_1 = A(\Omega^2 - 1 + \frac{\varepsilon_1A^2\Omega^2}{2} - \frac{3}{4}\varepsilon_2A^2)\cos(\Omega t) + (\frac{\varepsilon_1A^3\Omega^2}{2} - \frac{\varepsilon_2A^3}{4})\cos(3\Omega t) \quad (11)$$

In order to ensure that no secular terms appear in the next iteration, the resonance must be avoided. Therefore, the coefficient of $\cos \Omega t$ in Eq. (11) requires to be zero.

$$\Omega_1^2 = \frac{4 + 3\varepsilon_2A^2}{4 + 2\varepsilon_1A^2} \quad (12)$$

So, from Eq. (11), with initial conditions in Eq. (5), the following first-order approximate solution will be obtained:

$$u_1(t) = A \cos(\Omega_1 t) + \frac{A^3(2\varepsilon_1\Omega_1^2 - \varepsilon_2)}{32\Omega_1^2} (\cos(\Omega_1 t) - \cos(3\Omega_1 t)) \quad (13)$$

For n=1 into Eq. (3), with the initial functions in Eq. (4) and u_1 given by Eq. (13), the following differential equation is obtained for u_2 :

$$\begin{aligned} \ddot{u}_2 + \Omega^2u_2 = & A(\Omega^2 - 1 + \frac{\varepsilon_1A^2\Omega^2}{2} - \frac{3}{4}\varepsilon_2A^2 + \frac{A^4(2\varepsilon_1^2\Omega^4 - 5\varepsilon_1\varepsilon_2\Omega^2 + 2\varepsilon_2^2)}{64\Omega^2} - \dots \\ & \frac{A^4(2\varepsilon_1^2\Omega^2 - \varepsilon_1\varepsilon_2)}{16})\cos(\Omega t) + \\ & (\frac{\varepsilon_1A^3\Omega^2}{2} - \frac{\varepsilon_2A^3}{4} - \frac{A^5(2\varepsilon_1^2\Omega^4 - 5\varepsilon_1\varepsilon_2\Omega^2 + 2\varepsilon_2^2)}{128\Omega^2} - \dots \\ & \frac{19A^5(2\varepsilon_1^2\Omega^2 - \varepsilon_1\varepsilon_2)}{128})\cos(3\Omega t) + \\ & (-\frac{A^5(2\varepsilon_1^2\Omega^4 - 5\varepsilon_1\varepsilon_2\Omega^2 + 2\varepsilon_2^2)}{128\Omega^2} - \dots \\ & \frac{5A^5(2\varepsilon_1^2\Omega^2 - \varepsilon_1\varepsilon_2)}{128})\cos(5\Omega t) \end{aligned} \quad (14)$$

Avoiding the presence of a secular term requires:

$$\begin{aligned} \Omega_2 = & \frac{\sqrt{A_1 \times (A_2 + \sqrt{A_3})}}{A_4} \\ A_1 = & 32 + 16\varepsilon_1A^2 - 3\varepsilon_1^2A^4 \\ A_2 = & 64 + 48\varepsilon_2A^2 + \varepsilon_1\varepsilon_2A^4 \\ A_3 = & 4096 + 6144\varepsilon_2A^2 + 128\varepsilon_1\varepsilon_2A^4 + 1792\varepsilon_2^2A^4 - \\ & 160\varepsilon_1\varepsilon_2^2A^6 + 49\varepsilon_1^2\varepsilon_2^2A^8 \\ A_4 = & 64 + 32\varepsilon_1A^2 - 6\varepsilon_1^2A^4 \end{aligned} \quad (15)$$

Solving the Eq. (14) with the initial conditions in Eq. (5), the following equation will be achieved:

$$\begin{aligned}
 u_2(t) = & A \cos(\Omega_2 t) + \left(-\frac{34}{768} \varepsilon_1^2 A^5 + \right. \\
 & \frac{21}{768 \Omega_2^2} \varepsilon_1 \varepsilon_2 A^4 - \frac{24}{768 \Omega_2^2} \varepsilon_2 A^2 - \frac{2}{768 \Omega_2^4} \varepsilon_2^2 A^4 + \dots \\
 & \frac{48}{768} \varepsilon_1 A^2 \cos(\Omega_2 t) + \frac{A^5 (2 \varepsilon_1 \Omega_2^2 - \varepsilon_2)}{512 \Omega_2^4} \\
 & \times (10 \varepsilon_1 A^2 \Omega_2^2 - 16 \Omega_2^2 - \varepsilon_2 A^2) \cos(3 \Omega_2 t) + \dots \\
 & \left. \frac{A^5 (4 \varepsilon_1 \Omega_2^2 - \varepsilon_2)}{3840 \Omega_2^4} \cos(5 \Omega_2 t) \right) \quad (16)
 \end{aligned}$$

3. Results and discussions

To illustrate and verify the accuracy of MIPM, it compared with published data and exact solution. The exact frequency for a cantilever beam with considering nonlinear geometry can be derived as follows [29]:

$$\omega_{Exact} = \frac{2\pi}{4\sqrt{2}A \int_0^{\pi/2} \frac{\sqrt{1 + \varepsilon_1 A^2 \cos^2 t \sin t}}{\sqrt{A^2 (1 - \cos^2 t) (\varepsilon_2 A^2 \cos^2 t + \varepsilon_2 A^2 + 2)}} dt} \quad (17)$$




Fig. 1. The effect of ε_1 on position for $\varepsilon_2 = 1$ and $A = \frac{\pi}{3}$.

Figs. 1 and 2, show effects of constant parameters, ε_1 and ε_2 , on deflection of the cantilever beam considering nonlinearity geometric. It has been shown that the results are in very good adaptation with those obtained by the exact solution.

In addition, stability has been investigated in Fig. 3 and the phase diagram has been presented. By using of this method the treatment of the system investigation and study the stability and response based on constant parameters is very easy. In addition, by changing the constant parameters, It doesn't need to change the solution or solve the problem again.

Also, The effect of small parameters ε_1 and ε_2 on the frequency corresponding to various initial amplitudes has been studied in Figs.4 and 5.

Finally, The effect of different parameters $\varepsilon_1, \varepsilon_2$ and A are studied in Figs. 6 and 7 simultaneously.




Fig. 2. The effect of ε_2 on position for $\varepsilon_1 = 1$ and $A = \frac{\pi}{3}$.




Fig. 3. The phase plane to show the stability.




Fig. 4. Nonlinear frequency versus amplitude for various ϵ_1 , at $\epsilon_2 = 1$.




Fig. 5. Nonlinear frequency versus amplitude for various ϵ_2 , at $\epsilon_1 = 1$.




Fig. 6. Sensitivity analysis of frequency for $\epsilon_1 = 0.1$.




Fig. 7. Sensitivity analysis of frequency for $\epsilon_2 = 0.1$.

4. Conclusions

In this study, MIPM is given to analyse a cantilevered beam with nonlinearity geometric. The accurate results with few iterations are obtained, that reduce the computational cost. The excellent agreement of the MIPM solutions with exact solution shows the reliability and the efficiency of the method. This method accelerated the convergence of the solution. It is predicted, that MIPM may find wide applications in engineering problems. However, it needs more research to know the optimized application of this method on engineering problems, especially mechanical affairs.

References

- [1] Rehfield, L.W.A., "Simple approximate method for analysing nonlinear free vibrations of elastic structures", *J. Appl. Mech, ASME*, 42, 509-511, 1975.
- [2] Sathyamoorthy, M., "Nonlinear analysis of beams, Part II: Finite-element methods", *Shock Vib. Dig.* 14, 7-18, 1982.
- [3] Klein, L., "Transverse vibrations of non-uniform beam", *J. Sound Vibr.* 37, 491-505, 1974.
- [4] Downs, B., "Transverse vibrations of cantilever beam having unequal breadth and depth tapers", *J. Appl. Mech, ASME*, 44, 737-742, 1977.
- [5] Sato, K., "Transverse vibrations of linearly tapered beams with ends restrained elastically against rotation subjected to axial force", *Int. J. Mech. Sci*, 22, 109-115, 1980.
- [6] Lau, J.H., "Vibration frequencies of tapered bars with end mass", *ASME J. Appl. Mech*, 51, 179-181, 1984.
- [7] Lee, S.Y.; Kuo, Y.H., "Exact solution for the analysis of general elastically restrained non-uniform beams", *J. Appl. Mech, ASME*, 59, 205-212, 1992.
- [8] Kopmaz, O.; Gundogdu, O., "On the curvature of an euler-bernoulli beam", *International Journal of Mechanical Engineering Education*, 31, 132-142, 2003.
- [9] Pirbodaghi, T.; Ahmadian, M.T.; Fesanghary, M., "On the homotopy Analysis Method for Nonlinear Vibration of Beams", *Mechanics Research communications*, 36, 143-148, 2009.
- [10] Hojjati, M.H.; Jafari, S., "Semi-exact solution of non-uniform thickness and density rotating disks, Part II, Elastic strain hardening solution", *International J. Pressure Vessels and Piping*, 86, 307-318, 2009.
- [11] Mashinchi Joubari, M.; Asghari, R., "Analytical Solution for Nonlinear Vibration of Micro-Electro-mechanical System (MEMS) by Frequency-Amplitude Formulation Method", *The Journal of Mathematics and Computer Science*, 4(3), 371-379, 2012.
- [12] Baghani, M.; Fattahi, M.; Amjadian, A., "Application of the variational iteration method for nonlinear free vibration of conservative oscillators", *Scientia Iranica B*, 19(3), 513-518, 2012.
- [13] Rafei, M.; Ganji, D.D.; Daniali, H.; Pashaei, H., "The variational iteration method for nonlinear oscillators with discontinuities", *Journal of Sound and Vibration*, 305, 614-620, 2007.
- [14] He, J.H., "Some Asymptotic Methods for Strongly Nonlinear Equations", *International Journal of Modern Physics B*. 20(10), 1141-1199, 2006.
- [15] Özis, T.; Yildirim, A., "Generating the periodic solutions for forcing van der Pol oscillators by the Iteration Perturbation method", *Nonlinear Analysis, Real World Applications*, 10, 1984-1989, 2009.
- [16] Younesian, D.; KalamiYazdi, M.; Askari, H.; Saadatnia, Z., "Frequency Analysis of

- Higher-order Duffing Oscillator using Homotopy and Iteration-Perturbation Techniques”, 18th Annual International Conference on Mechanical Engineering, ISME, 2010.
- [17] Ganji, D.D., “The application of He’s homotopy perturbation method to nonlinear equations arising in heat transfer”, *Physics Letters A*, 355, 337-341, 2006.
- [18] He, J.H., “The homotopy perturbation method for non-linear oscillators with discontinuities”, *Appl Math Comput*, 151, 287-92, 2004.
- [19] Barari, A., Kaliji, H.D., Ghadimi, M., Do-mairry, G., “Non-linear vibration of Euler-Bernoulli beams”, *Latin American Journal of Solids and Structures*, 8, 139-148, 2011.
- [20] Ganji, S.S.; Barari, A.; Ganji, D.D., “Approximate analyses of two mass-spring systems and buckling of a column”, *Computers & Mathematics with Applications*, 61(4), 1088-1095, 2011.
- [21] Azami, R.; Ganji, D.D.; Babazadeh, H., “He’s Max-Min method for the relativistic oscillator and high order doffing equation”, *International journal of modern physics B*, 32, 5915-5927, 2009.
- [22] He, J.H., “Max-Min Approach to Nonlinear Oscillators”, *International Journal of Nonlinear Sciences and Numerical Simulation*, 9(2), 207-210, 2008.
- [23] Wu, B.S.; Sun, W.P.; Lim, C.W., “An analytical approximate technique for a class of strongly non-linear oscillators”, *International Journal of Non-Linear Mechanics*, 41, 766-774, 2006.
- [24] Mashinchi Joubari, M.; Asghari, R.; Zareian Jahromy, M., “Investigation of the Dynamic Behavior of Periodic Systems with Newton Harmonic Balance Method”, *The Journal of Mathematics and Computer Science*, 4, 418-427, 2012.
- [25] Joneidi, A.A.; Ganji, D.D.; Babaelahi, M., “Differential Transformation Method to determine fin efficiency of convective straight fins with temperature dependent thermal conductivity”, *International Communications in Heat and Mass Transfer*, 36, 757-762, 2009.
- [26] Momeni, M.; Jamshidi, N.; Barari, A.; Ganji, D.D., “Application of He’s Energy Balance Method to Duffing Harmonic Oscillators”, *International Journal of Computer Mathematics*, 88, 135-144, 2010.
- [27] Mehdipour, I.; Ganji, D.D.; Mozaffari, M., “Application of the energy balance method to nonlinear vibrating equations”, *Current Applied Physics*, 10, 104-112, 2010.
- [28] Marinca, V.; Herisanu, N., “A modified iteration perturbation method for some nonlinear oscillation problems”, *Acta Mechanica*, 184, 231-242, 2006.
- [29] Shahidi, M.; Bayat, M.; Pakar, I., Abdollahzadeh, G.R., “Solution of free non-linear vibration of beams”, *International Journal of Physical Sciences*, 6, 1628-1634, 2011.